

## MSP4

Помпа потопяема за сондажи

-  Clean water
-  Domestic use
-  Civil use
-  Agricultural use



### CONSTRUCTION CHARACTERISTICS

<b>DELIVERY BODY AND EXTERNAL SLEEVE</b>	Stainless steel AISI 304 complete with threaded delivery port in compliance with ISO 228/1.
<b>IMPELLERS</b>	Lexan 141-R
<b>DIFFUSERS</b>	Noryl FE1520PW
<b>STAGE CASING</b>	Stainless steel AISI 304
<b>PUMP SHAFT</b>	Stainless steel AISI 304
<b>DRIVE COUPLING</b>	Stainless steel AISI 316L
<b>MOTOR SHAFT</b>	Stainless steel EN 10088-3 1.4104 (AISI 431 for 1.1 kW single-phase)
<b>MOTOR SLEEVE</b>	Stainless steel AISI 304
<b>TWO MECHANICAL SEALS SEPARATED BY AN OIL CHAMBER</b>	<b>Motor side:</b> Ceramic - Graphite - NBR <b>Pump side:</b> Silicon carbide - Graphite - NBR
<b>POWER CABLE</b>	PBS-P type 20 m long power cable



### PERFORMANCE RANGE

- Flow rate up to **150 l/min** (9 m<sup>3</sup>/h)
- Head up to **128 m**

### APPLICATION LIMITS

- Maximum liquid temperature **+35 °C**
- Maximum sand content **150 g/m<sup>3</sup>**
- Maximum immersion depth of **60 m** with a sufficiently long power cable
- Vertical and horizontal installation
- Starts/hour: **20** at regular intervals
- Continuous service **S1**

### CONSTRUCTION AND SAFETY STANDARDS

EN 60335-1  
IEC 60335-1  
CEI 61-150

EN 60034-1  
IEC 60034-1  
CEI 2-3



### INSTALLATION AND USE

Suitable for pumping clean water from boreholes that contain sand (up to 150 g/m<sup>3</sup>).

Because of their high efficiency and reliability they are suitable for use in domestic applications such as domestic water supply as part of a pressure supply and for irrigation, etc.

### ABSORPTION


MODEL	VOLTAGE	
	230 V	240 V
<b>Single-phase</b>		
<b>MSP – 0.55 kW</b>	<b>5.0 A</b>	<b>4.8 A</b>
<b>MSP – 0.75 kW</b>	<b>6.0 A</b>	<b>5.8 A</b>
<b>MSP – 1.1 kW</b>	<b>8.0 A</b>	<b>7.8 A</b>

### PALLETIZATION

MODEL	GROUPAGE/CONTAINER
<b>Single-phase</b>	n. pumps
<b>2MSP07-4M</b>	<b>55</b>
<b>2MSP10-4M</b>	<b>33</b>
<b>2MSP15-4M</b>	<b>33</b>
<b>4MSP07-4M</b>	<b>55</b>
<b>4MSP10-4M</b>	<b>55</b>
<b>4MSP15-4M</b>	<b>33</b>
<b>6MSP07-4M</b>	<b>55</b>
<b>6MSP10-4M</b>	<b>55</b>
<b>6MSP15-4M</b>	<b>33</b>

## CHARACTERISTIC CURVES AND PERFORMANCE DATA

50 Hz | n = 2900 min<sup>-1</sup>



MODEL	POWER (P <sub>2</sub> )		Q	0	0.6	1.2	1.8	2.4	3.0	3.6
Single-phase	kW	HP	m <sup>3</sup> /h	0	10	20	30	40	50	60
2MSP07-4M	0.55	0.75	H metres	66	65	60	54	46	35	20
2MSP10-4M	0.75	1		86	85	79	71	60	45	26
2MSP15-4M	1.1	1.5		128	125	118	108	91	70	39

MODEL	POWER (P <sub>2</sub> )		Q	0	1.2	1.8	2.4	3.0	3.6	4.2	4.8	5.4	6.0
Single-phase	kW	HP	m <sup>3</sup> /h	0	20	30	40	50	60	70	80	90	100
4MSP07-4M	0.55	0.75	H metres	46	44	42	40	38	35	31.5	27	23	17
4MSP10-4M	0.75	1		60	56	54.5	52	49	45	40.5	35	29	23
4MSP15-4M	1.1	1.5		92	88	85	81	76	70	63	54.5	45	35

MODEL	POWER (P <sub>2</sub> )		Q	0	1.5	3.0	4.5	6.0	7.5	9.0
Single-phase	kW	HP	m <sup>3</sup> /h	0	25	50	75	100	125	150
6MSP07-4M	0.55	0.75	H metres	27	26	24	22	19	15	11
6MSP10-4M	0.75	1		40	38	36	33	29	24	17
6MSP15-4M	1.1	1.5		61	58	54	50	44	35	26

Q = Flow rate  
H = Total manometric head

Tolerance of characteristic curves in compliance with EN ISO 9906 Grade 3B.

## DIMENSIONS AND WEIGHT

MODEL	PORT DN	DIMENSIONS mm			kg
		N. STAGES	∅	h	
2MSP07-4M	1 1/4"	10	100	705	12.5
2MSP10-4M		13		786	14.3
2MSP15-4M		20		986	17.8
4MSP07-4M		7		674	12.1
4MSP10-4M		9		743	13.8
4MSP15-4M		14		925	17.0
6MSP07-4M		4		641	10.7
6MSP10-4M		6		725	13.3
6MSP15-4M		9		887	16.5

