Drum pump FP 424, sealless, not recommended for small solids, abrasive or crystallising liquids. 50 mm diameter options for high flow applications. G 1¼" male discharge connection, with FLUX-Clip, without hose connection.

in stainless steel (S)

for applications in Zone 0, Ex-marking II 1/2 G Ex h IIB T4...T3 Ga/Gb, with zone separation

- **FP 424 Ex S-43/38, FKM seal**, stainless steel shaft

immersion length	part no.	
700 mm	10-42422007	●
1.000 mm	10-42422010	●
1.200 mm	10-42422012	●

- **FP 424 Ex S-43/38, FEP seal**, stainless steel shaft

immersion length	part no.	
700 mm	10-42429307	●
1.000 mm	10-42429310	●
1.200 mm	10-42429312	●

- **FP 424 Ex S-43/38, EPDM seal**, stainless steel shaft

immersion length	part no.	
1.000 mm	10-42428010	●
1.200 mm	10-42428012	●

- **FP 424 Ex S-43/37 Z, FKM seal**, stainless steel shaft **(for increased pumping head)**

immersion length	part no.	
700 mm	10-42422107	●
1.000 mm	10-42422110	●
1.200 mm	10-42422112	●

- **FP 424 Ex S-43/37 Z, FEP seal**, stainless steel shaft **(for increased pumping head)**

immersion length	part no.	
700 mm	10-42429407	●
1.000 mm	10-42429410	●
1.200 mm	10-42429412	●

- **FP 424 Ex S-50/45 Z, FKM seal**, stainless steel shaft **(for increased pumping head)**

immersion length	part no.	
700 mm	10-42422207	●
1.000 mm	10-42422210	●
1.200 mm	10-42422212	●

- **FP 424 Ex S-50/45 Z, FEP seal**, stainless steel shaft **(for increased pumping head)**

immersion length	part no.	
700 mm	10-42429507	●
1.000 mm	10-42429510	●
1.200 mm	10-42429512	●



FP 424 Ex S

in stainless steel (S), HT version

for application in Zone 0, for ambient temperature to **+60 °C**, Ex-marking II 1/2 G Ex h IIB T4...T3 Ga/Gb, with zone separation

- **FP 424 Ex (HT) S-43/38 FKM** seal, stainless steel shaft

immersion length	part no.	
1.000 mm	10-42422310	●
1.200 mm	10-42422312	●

- **FP 424 Ex (HT) S-43/37 Z FKM** seal, stainless steel shaft **(for increased pumping head)**

immersion length	part no.	
1.000 mm	10-42422410	●
1.200 mm	10-42422412	●

- **FP 424 Ex (HT) S-50/45 Z FKM** seal, stainless steel shaft **(for increased pumping head)**

immersion length	part no.	
1.000 mm	10-42422510	●
1.200 mm	10-42422512	●

in polypropylene (PP)

- **F 424 PP-41/36, FKM seal, hastelloy C shaft**

immersion length	part no.	
700 mm	10-42440007	●
1.000 mm	10-42440010	●
1.200 mm	10-42440012	●

- **F 424 PP-41/36, FKM seal, titanium shaft**

immersion length	part no.	
700 mm	10-42440707	●
1.000 mm	10-42440710	●
1.200 mm	10-42440712	●

- **F 424 PP-41/36, EPDM seal, hastelloy C shaft**

immersion length	part no.	
700 mm	10-42448007	●
1.000 mm	10-42448010	●
1.200 mm	10-42448012	●

Other seal materials available on request

illustration with hose connection (not included)

* AdBlue® is a registered trademark of: Verband der Automobilindustrie e. V. (VDA)