

Технически характеристики



3M[™] Visitor Safety Glasses

Technical datasheet



Product description

The $3M^{\infty}$ Visitor Safety Spectacle consists of a single ocular and fixed-length temple arms. An integrated brow-guard and vented side-shield are included.

Key features

- Optical Class 1 to allow prolonged comfortable wear
- Integrated side-shield for maximum protection
- Integrated brow bar for added protection
- Can be worn over prescription spectacles
- Offers excellent protection against UV radiation
- Total weight (39g)

Product range

Product ID	Description	Lens colour	Frame colour
Visitor	3M [™] Visitor Safety Glasses with clear PC lens	Clear PC	Clear

Typical applications

These products can be used in a wide range of applications including:

- Construction
- ► Engineering
- General assembly
- Woodworking
- Light duty maintenance and repair

Intended use

These products are intended for protection against high speed particles at low energy (F) in accordance with EN 166:2001. These products also help protect against UV radiation in accordance with EN 170:2002.

The clear lens is intended to provide good colour recognition and excellent UV protection

Use limitation

- Never modify or alter this product
- Do not use this product against hazards other than those specified in this document
- In accordance with EN 166:2001 safety spectacles cannot be tested and approved for use against liquid droplets. Where liquid protection is specified a suitable product should be considered, for example safety goggles
- ► These products are not suitable for grinding or welding

Standards and approval

These products are type examined by BSI Group, Notified Body number 2797.

These products are CE marked to the requirements of European Regulation (EU) 2016/425.

The applicable legislation can be determined by reviewing the Certificates and Declarations of Conformity at www.3M.com/Eye/certs

Materials listing

Description	Material
Lens	Polycarbonate
Temple arms	Polycarbonate

Marking

The products have demonstrated compliance with the requirements of EN 166:2001 and associated standards and bear the following marks:

Product ref	Lens marking	Frame marking
Visitor	2C-1.2 3M 1 F	3M EN 166 F CE



Технически характеристики

3M™ Visitor Safety Glasses

Explanation of marking

Marking	Description
2C-1.2 (EN 170:2002)	UV protection This product conforms to the requirements of the standard, providing UV protection for the complete specified range (210nm – 365nm). Products marked C provide good colour recognition
1	Optical class
F	Impact protection against high speed particle at low energy (45m/s)

NOTICE **Notice** **Notice** **Notice** **Jortor** **Jortor**

IMPORTANT NOTICE

The use of the 3M product described within this document assumes that the user has previous experience of this type of product and that it will be used by a competent professional. Before any use of this product it is recommended to complete some trials to validate the performance of the product within its expected application.

All information and specification details contained within this document are inherent to this specific 3M product and would not be applied to other products or environment. Any action or usage of this product made in violation of this document is at the risk of the user.

Compliance to the information and specification relative to the 3M product contained within this document does not exempt the user from compliance with additional guidelines (safety rules, procedures). Compliance to operational requirements especially in respect to the environment and usage of tools with this product must be observed. The 3M group (which cannot verify or control those elements) would not be held responsible for the consequences of any violation of these rules which remain

Warranty conditions for 3M products are determined with the sales contract documents and with the mandatory and applicable clause, excluding any other warranty or

For more information on 3M products and services please contact 3M.