coverguard®

TECHNICAL DATASHEET
EURODIP 5030

Ref.   MO5030

Liquidproof

Latex

TYPE C

The +

Protection against low chemical risks and against radioactive contamination
Wet Grip
Flexibility
Intermittent use
Food contact

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
5027	7	10	100
5028	8	10	100
5029	9	10	100
5030	10	10	100

SALES PACKAGING

Hangable individual polybag

See also

VARIANTS

MO5020

DESCRIPTION

Natural yellow superior latex, thickness: 0.42mm,
Flocked cotton interior, anti-slip external finish, diamond shape,
long straight cuff,
Length: 30 cm

SECTORS

Farming, silviculture and fishing

Light Industries

Food-processing industry

Regional/public authorities

Maintenance

Services and distribution

APPLICATIONS

Household glove (daily cleaning),
Food industry (handling and preparation),
Communities work (cleaning, handling of household detergents),
mechanical industry (assembly of small parts)

coverguard®   EURODIP 5030   Ref. MO5030

TECHNICAL FEATURES

Color	Yellow
Shape	Glove
Gloves environment	Limited chemical protection
Glove type	Dipping
Material of coating	Latex
Tempered glove structure	Non supported
Interior finishing	Flocked
Support finition	Diamond
Type Of Cuff	Safety cuff / Scallop cut
Glove thickness - mm	0.42000
Length - mm	300

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 2777/10180-02/E00-00

Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park- Clonee- Dublin 15 Dublin Ireland

CE

EPI CAT. III

EN420:2003 + A1:2009   General requirements for protective gloves

EN388:2016   Protection from mechanical risks

1.0.0.0.X.

EN374-1:2016   Protection from chemical risks

Type C
K L
6 4

EN ISO 374-5:2016   Protection from bacteria and fungi

EN421:2010   Protective gloves against ionizing radiation