

coverguard®

TECHNICAL DATASHEET EUROWELD 140

Ref. 1WEL14

Specialties

Welding



The +

From size 9 to 11
Comfort
Antistatic
Good value for money

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
1WEL140009	9	10	60
1WEL140010	10	10	60
1WEL140011	11	10	60

SALES PACKAGING

>1

Multiple

DESCRIPTION

Split cowhide leather
Wing thumb
Safety cuff in split leather, length 15cm

SECTORS

Energy (production and distribution)
Maintenance
Construction - finishing work
Services and distribution

APPLICATIONS

Protection against contact heat up to 100°C for 15 seconds;
MMA welding (Rutile or cellulosic),
MAG/MIG welding (mixed gas or CO₂), coated wires; Plasma cutting, gouging, flame cutting work...

See also

VARIANTS



MO2507



MO2515

coverguard®

EUROWELD 140

Ref. 1WEL14

TECHNICAL FEATURES

Color	Grey	Glove thickness - mm	1.0 - 1.3mm
Shape	Glove	Cuff length - mm	150
Gloves environment	Moderate heat		
Glove type	Cut and sewn		
Glove construction	Welding		
Palm material	Leather		
Type of palm leather	Cowhide		
Finish palm leather	Split leather		
Back material	Leather		
Type of back leather	Cowhide		
Finish back leather	Split leather		
Type Of Cuff	Safety cuff / Straight cut		

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 2777/11676-03/E00-00

Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park- Clonree- Dublin 15 Dublin Ireland



EPI CAT. II

EN ISO 21420:2020

Protective gloves – General requirements and test methods

EN388:2016
+ A1:2018

Protection from mechanical risks



3.1.3.2 X

EN407:2020

Protective gloves and other hand protective equipments against thermal risks (heat and/or fire)



4.1.2. X. 4 X

EN12477:2001 + A1:2005
TYPE A

Protective gloves for welders

EN1149-2:1997

ESD safety gloves