

Ref. 6RSV520

Non Reusable



The +

FFP2 NR D, filters at least 94% of airborne particles.
Highly oil resistant.
Exhalation valve : better comfort with low resistance and moisture out.
Pass the dolomite clogging test.
Vertical folding and elastic tightening bands allow for a closer fit to the face.
Adjustable nose clip with micro-foam insert for a more precise and comfortable fit.
Electrostatic filtering media.
Each mask is individually protected.
Color-coded to identify the protection.

DESCRIPTION

Disposable vertical folding FFP2 mask in static-electro treated meltblown, woven elastic headstrap, adjustable nose bridge with micro foam insert, exhalation valve.

SECTORS

Mechanicals constructions
Light Industries
Regional/public authorities
Maintenance
Construction - finishing work

APPLICATIONS

For occasional use in very dusty environments. protection against non-toxic solid and liquid aerosols, such as calcium carbonate, kaolin, cement, cellulose, sulfur, cotton, flour, coal, ferrous metals, vegetable oils and soft woods (except hard woods such as exotic woods, etc.). textile industry, crafts, metallurgy, mining, underground public works, carpentry, cabinetmaking.

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
6RSV520NSI	-		20

SALES PACKAGING

Hangable box

See also

VARIANTS



6RSV530

TECHNICAL FEATURES

Shape	Flat foldable mask
Weight	13g
Color	White
Color 2	Blue

Features

FFP2 NR D with valve
Latex and PVC free.
Polypropylene exhalation valve.
Static-electro treated meltblown filtration material.
Woven elastics headstraps.
Adjustable nose bridge and micro-aperture foam.
Non-toxic and odorless marking.
No glue.
Flow at 95 l/min
5 years

Service life

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate
CE 815345

Delivered by BSI Group The Netherlands B.V (2797) Say Building- John M. Keynesplein 9- 1066 EP Amsterdam Netherlands



EPI CAT. III

EN149:2001 + A1:2009

Particle filtering half masks