

Тел Деса заваръчна за МИГ заваряване на нисколегирана стомана 0.8 мм, 0.7 кг, 60-200 А



Description

- Code: **010872** 0,7 Kg, Spool Ø 100mm, (Blister), (master box 4 pcs/pack)
- Code: **010805** 5,0 Kg, Spool Ø 200mm
- AWS A5.18: ER 70S-6
- EN ISO 14341-A: G 42 2 M G3Si1
- Current intensity **60 - 200 Amp**
- Shielding gas (**Argon / CO2**) - (**CO2**)
- **Main application**
- Suitable for the joint of unalloyed carbon steels. To be used for steel structures in general, carbody repair, tanks, etc.

Features

LOGISTIC INFO CODE: 010872

Barcode: 8011399001501

Package dimension, Wid.-Dep.-Height (mm): 130 x 50 x 170

Package weight kg: 0,8

Master box dimension, Wid.-Dep.-Height (mm): 260 x 120 x 150

Master box weight kg: 3,4

Pieces for master box: 4

HS code: 83119000

LOGISTIC INFO CODE: 010805

Barcode: 8011399001433

Package dimension, Wid.-Dep.-Height (mm): 215 x 210 x 65

Package weight kg: 5,4

HS code: 83119000

Продукт: [Тел Деса заваръчна за МИГ заваряване на нисколегирана стомана 0.8 мм, 0.7 кг, 60-200 А](#)

Категория: [Електродъгово заваряване](#)

Бранд: [Деса](#)

Категория бранд: [Тел Деса](#)