

Горещовалцуван профил - кръгъл плътен

D диаметър / мм	Линейно тегло кг/м.	D диаметър / мм	Линейно тегло кг/м.	D диаметър / мм	Линейно тегло кг/м.
8,0	0,39	30,0	5,55	95,0	55,64
9,0	0,50	32,0	6,31	100,0	61,65
10,0	0,62	35,0	7,55	105,0	67,97
11,0	0,75	38,0	8,90	110,0	74,60
12,0	0,89	40,0	9,86	115,0	81,54
13,0	1,04	42,0	10,88	120,0	88,78
14,0	1,21	45,0	12,48	125,0	96,33
15,0	1,39	48,0	14,21	130,0	104,19
16,0	1,58	50,0	15,41	135,0	112,36
17,0	1,78	55,0	18,65	140,0	120,84
18,0	2,00	60,0	22,20	145,0	129,63
19,0	2,23	65,0	26,05	150,0	138,72
20,0	2,46	70,0	30,21	160,0	157,80
22,0	2,98	75,0	34,68	170,0	178,20
24,0	3,55	80,0	39,46	180,0	199,80
25,0	3,85	85,0	44,54	190,0	222,60
28,0	4,83	90,0	49,94	200,0	246,60

Ташев-Галвинг
www.tashev-galving.com