




CANTILEVER ARM SSA2,0 30x30



Usage: universal channel system for building fastening systems, with repeatable perforation; with cut centimeter scale on the channel side.



electro-galvanized



steel S235JR



Permissible load

Length L [mm]	Weight [kg]	Designation for the order	Catalogue number
150	0,390	SSA2,0L150	80930301500
250	0,520	SSA2,0L250	80930302500
300	0,590	SSA2,0L300	80930303000
350	0,660	SSA2,0L350	80930303500
450	0,800	SSA2,0L450	80930304500
500	0,860	SSA2,0L500	80930305000
750	1,200	SSA2,0L750	80930307500
1000	1,540	SSA2,0L1000	80930300000

Detailed information referring to maximum recommended loads are specified in [Chapter 20](#).


Lining strip is available for the channel on [page 91](#).

CHANNELS

SSA2,0

SSMG2,0

CANTILEVER ARM SSMG2,0 41x21



Usage: universal channel system for building fastening systems, with repeatable perforation and serrated edges in order to lock the accessories better; they have a cut centimeter scale on the channel side.



electro-galvanized



steel S235JR



Permissible load

Length L [mm]	Weight [kg]	Designation for the order	Catalogue number
240	0,580	SSMG2,0L240	80941212400
320	0,690	SSMG2,0L320	80941213200
400	0,810	SSMG2,0L400	80941214000
480	0,920	SSMG2,0L480	80941214800
560	1,040	SSMG2,0L560	80941215600
800	1,380	SSMG2,0L800	80941218000

Detailed information referring to maximum recommended loads are specified in [Chapter 20](#).

Lining strip is available for the channel on [page 91](#).