




## CHANNEL SZME3,0 50x80



Permissible load

**Usage:** universal channel system for building fastening systems, with repeatable perforation and serrated edges in order to lock the accessories better; they have a cut centimeter scale on the channel side.

Sendzimir galvanized

S250GD steel

| Length<br>L [mm] | Weight<br>[kg] | Designation<br>for the order | Catalogue<br>number |
|------------------|----------------|------------------------------|---------------------|
| 2000             | 9,800          | SZME3,0L2000                 | 80750803020         |
| 3000             | 14,700         | SZME3,0L3000                 | 80750803030         |
| 4000             | 19,600         | SZME3,0L4000                 | 80750803040         |
| 6000             | 29,400         | SZME3,0L6000                 | 80750803060         |

Detailed information referring to maximum recommended loads are specified in [Chapter 20](#).

Lining strip is available for the channel on [page 91](#).

CHANNELS

SZME3,0

SDMG2,0

SDMF2,5

SDMF2,5

SDMF2,5

SDMF2,5

SDMF2,5

SDMF2,5

SDMF2,5

SDMF2,5

SDMF2,5

SDMF2,5

SDMF2,5


SDMF2,5

SDMF2,5

SDMF2,5

SDMF2,5

## DOUBLE CHANNEL SDMG2,0 41x42



Permissible load

**Usage:** universal channel system for building fastening systems; with repeatable perforation and serrated edges in order to lock the accessories better; with cut centimeter scale on the channel side.

Sendzimir galvanized


S250GD steel

| Length<br>L [mm] | Weight<br>[kg] | Designation<br>for the order | Catalogue<br>number |
|------------------|----------------|------------------------------|---------------------|
| 2000             | 5,720          | SDMG2,0L2000                 | 80841422020         |
| 3000             | 8,580          | SDMG2,0L3000                 | 80841422030         |
| 4000             | 11,440         | SDMG2,0L4000                 | 80841422040         |
| 6000             | 17,160         | SDMG2,0L6000                 | 80841422060         |

Detailed information referring to maximum recommended loads are specified in [Chapter 20](#).

Lining strip is available for the channel on [page 91](#).

## DOUBLE CHANNEL SDMF2,5 41x82



Permissible load

**Usage:** universal channel system for building fastening systems, with repeatable perforation and serrated edges in order to lock the accessories better; they have a cut centimeter scale on the channel side.

Sendzimir galvanized

S250GD steel

| Length<br>L [mm] | Weight<br>[kg] | Designation<br>for the order | Catalogue<br>number |
|------------------|----------------|------------------------------|---------------------|
| 2000             | 10,400         | SDMF2,5L2000                 | 80841822520         |
| 3000             | 15,600         | SDMF2,5L3000                 | 80841822530         |
| 4000             | 20,800         | SDMF2,5L4000                 | 80841822540         |
| 6000             | 31,200         | SDMF2,5L6000                 | 80841822560         |

Detailed information referring to maximum recommended loads are specified in [Chapter 20](#).

Lining strip is available for the channel on [page 91](#).