




CHANNEL SZMF1,5 41x41



||||| Permissible load

Usage: universal channel system for building fastening systems; with repeatable perforation and serrated edges in order to lock the accessories better; with cut centimeter scale on the channel side.

Sendzimir galvanized


S250GD steel

Length L [mm]	Weight [kg]	Designation for the order	Catalogue number
2000	3,180	SZMF1,5L2000	80741411520
3000	4,770	SZMF1,5L3000	80741411530
4000	6,360	SZMF1,5L4000	80741411540
6000	9,540	SZMF1,5L6000	80741411560

Detailed information referring to maximum recommended loads are specified in [Chapter 20](#).

Lining strip is available for the channel on [page 91](#).

CHANNEL SZMF2,0 41x41



||||| Permissible load

Usage: universal channel system for building fastening systems; with repeatable perforation and serrated edges in order to lock the accessories better; with cut centimeter scale on the channel side.

Sendzimir galvanized


S250GD steel

Length L [mm]	Weight [kg]	Designation for the order	Catalogue number
2000	4,200	SZMF2,0L2000	80741412020
3000	6,300	SZMF2,0L3000	80741412030
4000	8,400	SZMF2,0L4000	80741412040
6000	12,600	SZMF2,0L6000	80741412060

Detailed information referring to maximum recommended loads are specified in [Chapter 20](#).

Lining strip is available for the channel on [page 91](#).

CHANNEL SZMF2,5 41x41



||||| Permissible load

Usage: universal channel system for building fastening systems; with repeatable perforation and serrated edges in order to lock the accessories better; with cut centimeter scale on the channel side.

Sendzimir galvanized

S250GD steel

Length L [mm]	Weight [kg]	Designation for the order	Catalogue number
2000	5,200	SZMF2,5L2000	80741412520
3000	7,800	SZMF2,5L3000	80741412530
4000	10,400	SZMF2,5L4000	80741412540
6000	15,600	SZMF2,5L6000	80741412560

Detailed information referring to maximum recommended loads are specified in [Chapter 20](#).

Lining strip is available for the channel on [page 91](#).