



| Равностранен L профил /винкел/<br>DIN 1028 ST 37, ST 37-1, ST 37-2 |            |                      |
|--|------------|----------------------|
| Размер мм  |            |                      |
| b/s  | Тегло кг/м | Площ см <sup>2</sup> |
| 15 / 3   | 0.68       | 0.81                 |
| 20 / 3   | 0.88       | 1.12                 |
| 25 / 3   | 1.11       | 1.42                 |
| 25 / 4   | 1.45       | 1.85                 |
| 30 / 3   | 1.35       | 1.74                 |
| 30 / 4   | 1.77       | 2.27                 |
| 35 / 3   | 1.61       | 2.04                 |
| 35 / 4   | 2.1        | 2.67                 |
| 40 / 3   | 1.86       | 2.35                 |
| 40 / 4   | 2.42       | 3.08                 |
| 40 / 5   | 2.97       | 3.79                 |
| 45 / 5   | 3.38       | 4.3                  |
| 45 / 6   | 4          | 5.09                 |
| 50 / 5   | 3.77       | 4.8                  |
| 50 / 6   | 4.47       | 5.69                 |
| 50 / 7   | 5.15       | 6.56                 |
| 55 / 5   | 4.18       | 5.32                 |
| 60 / 6   | 5.42       | 6.91                 |
| 60 / 8   | 7.09       | 9.03                 |
| 70 / 7   | 7.38       | 9.4                  |
| 70 / 9   | 9.34       | 11.9                 |
| 75 / 7   | 7.94       | 10.1                 |
| 80 / 8   | 9.66       | 12.3                 |
| 80 / 10  | 11.9       | 15.1                 |
| 90 / 9   | 12.2       | 15.5                 |
| 100 / 10   | 15.1       | 19.2                 |
| 100 / 12   | 17.8       | 22.7                 |
| 110 / 10   | 16.6       | 21.2                 |
| 120 / 12   | 21.6       | 27.5                 |
| 140 / 14   | 29.5       | 37.2                 |
| 150 / 12   | 27.3       | 34.8                 |
| 150 / 15   | 33.8       | 43                   |
| 160 / 15   | 36.2       | 46.1                 |
| 160 / 16   | 43.5       | 55.4                 |