

## Обувки Coverguard работни с композитно бомбе и противопрободна подметка ниски 44, Galena



### PURCHASE PACKAGING

| REF        | EU | US   |    |
|------------|----|------|----|
| 9GAL500038 | 38 | 5.5  | 10 |
| 9GAL500039 | 39 | 6    | 10 |
| 9GAL500040 | 40 | 7    | 10 |
| 9GAL500041 | 41 | 8    | 10 |
| 9GAL500042 | 42 | 8.5  | 10 |
| 9GAL500043 | 43 | 9.5  | 10 |
| 9GAL500044 | 44 | 10   | 10 |
| 9GAL500046 | 46 | 11.5 | 10 |
| 9GAL500047 | 47 | 12.5 | 10 |

GALENA is a low safety shoe inspired by sport. It features an upper made of perforated suede leather and a lining in Polyester mesh which provide high breathability. The sides retro-reflective strips improves wearer safety.

The outsole resists to fuel and oil contact. It is slip resistant on ceramic or steel floor and offer protection and stability to the wearer. Its PU/PU double density construction provides comfort and durability. The insole made of textile fabric and EVA with holes guarantees an efficient cushioning and breathability. This model is equipped with a steel toe-cap and anti-penetration plate. GALENA is ideal for working dry environments..

9GAL140

### SECTORS

**Service Second work Handyman**

**Transport and logistics**

### APPLICATIONS EXAMPLES

- Painter,
- Electrician,
- Storekeeper, ...

## TECHNICAL FEATURES

|                                  |  |                              |                                 |
|----------------------------------|--|------------------------------|---------------------------------|
| <b>Closure</b>                   | Lacing                                 | <b>Anti perforation sole</b> | Steel                           |
| <b>Toe cap</b>                   | Steel                                  | <b>Perforated upper</b>      | Ventilation eyelets on the side |
| <b>Examples of applications</b>  | Painter, Electrician, Storekeeper, ... | <b>Color</b>                 | Grey/Black                      |
| <b>Upper</b>                     | Suede leather micro-perforated         | <b>Insole</b>                | Removable, perforated EVA       |
| <b>Loops eyelets</b>             | Metal                                  |                              |                                 |
|                                  | <b>Midsole</b>                         |                              |                                 |
|                                  | Injected                               |                              |                                 |
| polyurethane <b>Wearing sole</b> |  |                              |                                 |
|                                  | Polyurethan                            |                              |                                 |
| e                                | <b>Main</b>                            |                              |                                 |
| <b>assembly</b>                  | Injected                               |                              |                                 |
| assembly <b>Lining</b>           | Breathable                             |                              |                                 |
| 3D mesh                          |  |                              |                                 |

## INSTRUCTIONS FOR USE AND STORAGE

### Instructions for use :

- These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

### Storage instructions :

- Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

### Cleaning instructions :

- Regularly clean the shoes by using brushes, cleaning clothes.

## LEGISLATION

EN ISO 20345:2011

**S1P SRC**

**S1P** : Closed heel, antistatic shoe, fuel and oil resistant contact outsole, energy absorbing heel, puncture resistant midsole, resistant to a 1 100 Newtons pressure

**SRC** : Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

PPE CAT. II

Major risks

Продукт: [Обувки Coverguard работни с композитно бомбе и противопрободна подметка ниски 44, Galena](#)

Категория: [Лични предпазни средства на краката](#)

Бранд: [Coverguard](#)

Категория бранд: [Обувки Coverguard](#)