

## Обувки Coverguard работни с композитно бомбе и противопрободна подметка ниски №44, Milerite S1P



The +

- \* Sporty style
- \* Breathability
- \* Front reinforcement
- \* PU2D injected sole

### PURCHASE PACKAGING

Référence	Taille	Carton
9MIL280038	38	10
9MIL280039	39	10
9MIL280040	40	10
9MIL280041	41	10
9MIL280042	42	10
9MIL280043	43	10
9MIL280044	44	10
9MIL280045	45	10
9MIL280046	46	10
9MIL280047	47	10

#### DESCRIPTION

MILERITE S1P is a low safety shoe inspired by sport design with mesh upper and lining which offer high breathability and comfort. The front reinforcement made of embossed leather is suitable for users working squatting or kneeling. It ensures longer lifetime.

Its double density PU outsole resists to fuel and oil contact. It is slip-resistant on ceramic or steel floor and offers excellent shock absorption. Its removable insole, made of textile and EVA with wide perforations, offers good evacuation of perspiration.

MILERITE features a toe-cap and an anti-penetration plate made of steel for optimal protection.

It is ideal for work dry environments.

SECTORS

APPLICATIONS

## TECHNICAL FEATURES

Color	Blue	Closing	Lacing closure
Color 2	Green	Lining	Breathable 3D mesh
Upper	Mesh		
Toecap	Steel		
Puncture resistant sole	Stainless steel		
Midsole	PU		
Outsole	PU		
Insole	Removable, perforated EVA		
Main assembly	Injected		

## INSTRUCTION FOR USE AND STORAGE

### Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

### Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

### Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

## STANDARD(S)



EPI CAT. II

EN ISO 20345:2011

S1P

### Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe  $0,1M\Omega < A < 1000 M\Omega$  + Fuel and oil resistant contact outsole + Energy absorbing heel  $E \geq 20$  Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

Продукт: [Обувки Coverguard работни с композитно бомбе и противопрободна подметка ниски №44, Milerite S1P](#)

Категория: [Лични предпазни средства на краката](#)

Бранд: [Coverguard](#)

Категория бранд: [Обувки Coverguard](#)