



## Technical Data

Modell:	S 3 Ecoline	S 3 L Ecoline	S 3 L Mobileline
Crimp force (kN/Ton)	1200/120	1800/180	1800/180
Greaseless	✓	✓	✓
Control	Control A (Micr.)	Control A (Micr.)	Control A (Micr.)
SAE R 12 / 4SP* 1 piece fitting	1½ "	1½ "	1½ "
SAE R 12 / 4SP* 2 piece fitting	1¼ "	1½ "	1½ "
SAE R 15 / 4SH* 2 piece fitting	1"	1¼ "	1¼ "
Industrial*	2 "	2 "	2 "
90° Elbows*	1½ "	1¼ "	1¼ "
Max. Crimp range	70 mm	70 mm	70 mm
Opening	+ 35 mm	+ 27 mm	+ 27 mm
Opening without dies	105 mm	97 mm	97 mm
Type of dies	239-xx	239-xx	239-xx
Speed (mm/sec.)			
Close	4	2	1,5
Crimp	4	2	0,4
Open	6,5	7,6	5,7
Noise level (dBA)	69	69	69
Drive	3 kW	3 kW	1,8 kW
Oil	35 l	35 l	4 l
L x W x H Machine (mm)	592 x 545 x 672	600 x 550 x 630	430 x 370 x 440
Weight	150 Kg	150 Kg	110 Kg