

ProMax means ultimate performance, long-run times and durability. These heavy-duty generators are ideal for industrial and commercial work thanks to the professional VANGUARDTM Engine.



Starting Watts* - 7500 Running Watts** - 6000 Run time - 7h 5m Engine - Vanguard™ 479cc

Performance	6	
Starting (W)*	7500	
Running (W)**	6000	
Voltage / Frequency	230V / 50Hz	
Features		
Noise level dB/7m @ 25% load	72	
Run time @ 50% load	7h 5m	
Alternator	Power Surge TM / AVR	
Automatic low-oil shut down	Yes	
Voltmeter	Yes	
Oil filter	Yes	
Lubrication system	Yes	
Circuit breaker	Yes	
Frame	38mm Steel tubing	

Portability	Optional wheelkit and a telescopic handle
Dry weight (kg)	121
L x W x H (cm)	89 x 59 x 55
Warranty generator	2 years limited commercial***
SOCKETS	
Household sockets	2x 230V / 16 Amp
	1x 230V / 32 Amp
Engine	
Engine type	VANGUARD TM V-Twin OHV
Engine capacity	479cc
Cylinder	Cast Iron sleeve
Fuel tank capacity (l)	15
Fuel gauge	Yes
Starter	Electric Start - Key
Muffler	Quiet GenSet muffler
* Starting Watts is the maximum c motor, multiplied by the generator	current that can momentarily be supplied when starting a 's rated voltage.
** Per EN 12601:2010	N (9)