





REF.	FA 50 101 17
CE	EN 362:2004 Class B & M
	25 kN / 18 mm
MAT.	
	SCREW
KEYLOCK	---
+	---
	0.16 KG



**Résistance à la rupture / Ouverture**  
 Breaking strength / Gate opening  
**Resistencia a la ruptura / Apertura**  
 Resistenza alla rottura / Apertura  
**Bruchfestigkeit / Öffnung**

**MAT.**

**Matière**  
 Material  
**Material**  
 Materia  
**Material**



**Type d'ouverture**  
 Opening system  
**Tipo de apertura**  
 Sistema di apertura  
**Öffnungssystem**

<b>HS CODE</b>
73269098
<b>CARTON SIZE / PCS.</b>
38x28x23/100
<b>AET (EU) N°2777/10347-02/E03-01</b>
<b>Satra Technology Europe Ltd., N° 2777,</b> Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
<b>MODULE D F114/14003.02</b>
<b>SGS Fimko Oy, N°0598</b> Takomotie 8, 00380 HELSINKI, Finland
<b>AET (UKCA) N°AB0321/16053-01/E01-01</b>
<b>Satra Technology Centre, N°0321</b> Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
<b>MODULE D 11 IN14/14003</b>
<b>SGS United Kingdom Ltd., N°0120</b> Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom