

INDUSTRY LINE Electricity can be of vital importance in the agricultural sectors, farms, an auxiliary source of energy in buildings or for installation in a vehicle. Be prepared and equip your business with movable and reliable REM generators to ensure backup power for non-stop performance. Each component has been carefully designed and manufactured to optimize its contribution to the performance, reliability of the overall unit.

GSEm 7250 TBE

- Heavy-duty, never flat wheels with Strong frame (32 mm)
- Low-oil level shutdown – automatically safeguards engine from damage
- AVR System
- Quite operation
- 3in1 meter for rental services
- Touch electric start – battery included
- Large-capacity steel fuel tank with incorporated fuel gauge provides durability and extended run times
- Three-phase socket
- Cooper wire alternator



GSEm 12500 TBE

- Heavy-duty, never flat wheels with Strong frame (32 mm)
- Low-oil level shutdown – automatically safeguards engine from damage
- AVR System
- Quite operation
- 3in1 meter for rental services
- Touch electric start – battery included
- Large-capacity steel fuel tank with incorporated fuel gauge provides durability and extended run times
- Three-phase socket
- Cooper wire alternator



MODEL	GSEm 7250 TBE	GSEm 12500 TBE
OUTPUT MAX.POWER (kW 230 V)	5,0 (2 x 2,5)	9,9 (3 x 3,3)
OUTPUT MAX.POWER (kW 400 V)	7,25	10
OUTPUT RATED POWER (kW 230 V)	4,5 (2 x 2,25)	9 (3 x 3,0)
OUTPUT RATED POWER (kW 400 V)	6,75	9
RATED CURRENT (A)		
DISPLACEMENT (ccm)	420	680
ENGINE POWER (kW/HP)	11,1/15,0	14,5/19,5
OIL CAPACITY (l)	1,1	2
FUEL CAPACITY (l)	23	35
CONTINUOUS RUNNING TIME (h)	8	9
NOISE LEVEL (dB(A))	82	77
DIMENSIONS LxWxH (mm)	705x535x585	820x795x860
WEIGHT (kg)	87	123
ORDER NUMBER	39072500515	39125000515
EAN	3831081035721	3831081035738