












BC-3000.1, BC-3000 / GŁOWICE ZACZEPOWE / COUPLING HEADS

PARAMETRY PARAMETERS	KORPUS / HOUSING	WYMIARY / DIMENSIONS					INDEX / INDEX			RYSUNEK / DRAWING		
		A [mm]	B [mm]	ØD1 [mm]	ØD2 [mm]	C [mm]	L [mm]	dźwignia stalowa	dźwignia stalowa z wbudowanym zamkiem		dźwignia odlewana z nakładką	
D=27 kN S=150 kg DMC=3000 kg	STAL / STEEL		50	12,5	12,5		216					
		Ø 50,5	50	14,5	12,5		216	BC-3000.1C-01-00	BC-3000.1C-01-01			
			50	14,5	14,5		216	BC-3000.1C-02-00	BC-3000.1C-02-02			
		Ø 50,5	48+54	12,5	12,5	40	218	BC-3000.1D-00-00	BC-3000.1D-00-01			
												
D=27 kN S=150 kg DMC=3000 kg	ODLEW / CAST	Ø 50,5	40	12,5			214	BC-3000B-00-00	BC-3000B-00-01	BC-3000B-00-02 + SD		
			40	14,5			214	BC-3000B-01-00	BC-3000B-01-01	BC-3000B-01-02 + SD		
		Ø 50,5	44+54	12,5			224	BC-3000C-00-00	BC-3000C-00-01	BC-3000C-00-02 + SD		
			44+54	14,5			224	BC-3000C-01-00	BC-3000C-01-01	BC-3000C-01-02 + SD		
												
				Ø 60,5	40	12,5			214	BC-3000D-00-00	BC-3000D-00-01	BC-3000D-00-02 + SD
		40	14,5				214	BC-3000D-01-00	BC-3000D-01-01	BC-3000D-01-02 + SD		