

[A]

Scaffold attachment for hoist

For better distribution of the stress on the scaffold caused by using the hoist. Equipped with plate for locking the work positioning lever.



[B]

Internal adjustable prop (2.45 m to 3.3 m)

For using the hoists indoors or where there are no external scaffolding structures; height adjustable from a min. of 2.45 m to a max. of 3.3 m.



[C]

Window prop

Useful at construction sites or for refurbishment jobs with little work space. Easy and quick installation without using assembly tools.



[D]

External prop for hoists with max. capacity 200 kg

To install hoists outdoors without overhanging support points; consisting of an internal adjustable prop and conversion kit with ballast container. Ballast container dimensions: P460xL2500xH415 mm



		A	B	C	D
Max. capacity with extendible bracket hoist	kg	200	200	200	200
Max. capacity with fixed bracket hoist and swivelling extension	kg	200	200	-	200
Max. capacity with ext. bracket hoist and swivelling extension	kg	150	150	-	150
Weight	kg	18	44	44	85
w/l/h	mm	210/180/1950	540/540/2630	640/340/1320	2505/1400/2630

[E]

Gantries with capacity 300 kg (E1) and 500 kg (E2)

Suitable for all IMER hoists, except for RIO 100, Airone 200N and Airone 300N



[F]

Swivelling extensions

- For prop clamp attachment with work positioning lever for Rio 100 (F1)
- For prop hoist attachment with work positioning lever (F2)

For lifting bulky material with fixed bracket hoists, allowing the loading distance to be increased 360 mm; for increasing the loading distance with extendible bracket hoists up to 1,480 mm, with carrying capacity reduced to 150 kg.



[F1]



[F2]

[G]

Hoist trolley



[H1] Two-bucket carrier

[H2] Four-bucket carrier



[I]

Three-way scaffold frame lifting hook



[L]

Wedge-shaped bucket 45/90/120 litres



[M]

Scaffold clamps



[N]

90-litre bucket with bottom discharge



		E1	E2	F1	F2	G	H1	H2	I	L	M	N
Maximum capacity	kg	300	500	100	200	-	70	150	60	150/200/300	200	200
Weight	kg	-	-	7	13	8	4/8	3	3	12/15/19	25	
Width	mm	2310	2310	120	90	450	340	820	65	400/420/450	-	660
Length	mm	3170	3280	700	680	875	810	820	360	460/615/720	-	660
Height	mm	2250	2260	445	275	430	450	450	410	310/370/430	-	720