

Silverline Stira S Series A Hand chain hoist

Capacity 500 - 5000 kg

The Silverline Stira S Series A is designed and built for quality and safe, efficient operation. The arrangement of the spur gear drive allows a compact unit with very small dimensions. A lightweight hoist with low maintenance – and at economical price.

Features

- Low headroom permits optimal usage of available space.
- One guide roller and a heat treated load sheave with 4 precision machined chain pockets ensure smooth operation of the chain.
- The construction prevents a blocking and slipping of the hand chain.
- Roller and ball bearings at all rotating parts reduce friction loss and increase smooth operation and efficiency.
- Zinc-plated load chain as standard for added corrosion protection.
- Drop forged suspension and load hooks are made from non-aging, high tensile steel and fitted with robust safety latches.



INFO

Yale hoists and trolleys are not designed for passenger elevation applications and must not be used for this purpose.

Technical data Silverline Stira S Series A

| Model | Art.-No. | Capacity kg | Number of chain falls | Chain dimensions d x p mm | Pull on hand chain at WLL daN | Weight at standard lift (3 m) kg |
|--------------|-----------|----------------|--------------------------|------------------------------------|--|---|
| Stira S 500 | 192104564 | 500 | 1 | 6 x 18 | 26 | 8.7 |
| Stira S 1000 | 192104565 | 1000 | 1 | 6 x 18 | 36 | 10.6 |
| Stira S 2000 | 192104566 | 2000 | 1 | 8 x 24 | 39 | 16.0 |
| Stira S 3000 | 192104567 | 3000 | 2 | 8 x 24 | 41 | 23.4 |
| Stira S 5000 | 192104568 | 5000 | 2 | 10 x 30 | 44 | 37.5 |

Dimensions Silverline Stira S Series A

| Model | Stira S 500 | Stira S 1000 | Stira S 2000 | Stira S 3000 | Stira S 5000 |
|-------|----------------|-----------------|-----------------|-----------------|-----------------|
| A, mm | 289 | 334 | 347 | 524 | 610 |
| B, mm | 16 | 21 | 30 | 35 | 45 |
| C, mm | 22 | 27 | 34 | 37 | 46 |
| D, mm | 120 | 142 | 178 | 178 | 210 |
| E, mm | 120 | 142 | 178 | 178 | 210 |
| F, mm | 106 | 122 | 139 | 139 | 162 |

