



## 284




**APPLICATION:** for cutting and dividing tubes, drawn products and solid blocks.

**MACHINES:** table saws, single or double mitre saws with mechanical clamping of the workpiece.

**MATERIAL:** aluminium, brass, copper alloys, plastic, composite materials.

**WARNING:** it is recommended to properly clamp the workpiece during cutting operations and to use a liquid lubricant.  
Wax stick for lubrication NOT RECOMMENDED.

	ISO:	<b>K10</b>
	HV10:	<b>1.765</b>
	N/mm <sup>2</sup> :	<b>2.150</b>



### Saw blades for portable machines. Positive hook angle

D mm	B mm	Pin Hole 	Z	K mm	P mm	$\alpha$	$\beta$	ORDER NO.
160	20	-	24	2,2	1,6	5°	TCG	Y284.160.24H
190	30	-	30	2,6	2,2	5°	TCG	Y284.190.30M

Remarks: in plastic carry case.

### Saw blades for industrial machines. Positive hook angle

D mm	B mm	Pin Hole 	Z	K mm	P mm	$\alpha$	$\beta$	ORDER NO.
250	32	2/12/64	80	3,2	2,5	5°	TCG	284.080.10P
300	32	2/12/64	96	3,2	2,5	5°	TCG	284.096.12P
350	32	2/12/64	92	3,2	2,5	5°	TCG	284.092.14P
350	32	2/12/64	108	3,2	2,5	5°	TCG	284.108.14P
400	32	2/12/64	96	3,8	3,2	5°	TCG	284.096.16P
420	32	2/12/64	96	3,8	3,2	5°	TCG	284.096.17P
450	32	2/12/64	108	3,8	3,2	5°	TCG	284.108.18P
500	32	2/12/64	120	4,0	3,2	5°	TCG	284.120.20P

Remarks: in cardboard box.

Ташев-Галвинг ООД  
www.tashev-galving.com