PROLINE SAW CHAINS



All Hitachi saw chains are fabricated from special alloy steel. This specially engineered steel adds toughness and abrasion resistance. All Hitachi saw chain cutters are plated with hard industrial chrome. This process yields superior edge-holding qualities to other types of plating. In the field, Hitachi saw chains stay sharp longer.

Unlike the competition, every Hitachi saw chain is sharpened after assembly to cut fast out of the box. To reduce bearing wear during "break in", all Hitachi chains are injected at the rivet bearing with a hypoid lubricant

	Pitch inch	Gauge mm (inch)	Length cm (inch)	Nr. of links	PQ	MOQ	Item number	Barcode
(manner manner)	1/4" LP	1.3 (.050")	25 (10")	60	1	1	781110	8717574035100
(management of the second of t	3/8" LP	1,3 (.050")	25 (10")	40	1	1	781120	8717574021301
	3/8" LP	1,3 (.050")	30 (12")	45	1	1	781122	8717574021318
	3/8" LP	1,3 (.050")	35 (14")	52	1	1	781124	8717574021325
	3/8" LP	1,3 (.050")	40 (16")	57	1	1	781126	8717574021332
()	.325" NK	1,3 (.050")	33 (13")	56	1	G	781133	8717574021349
	.325" NK	1,3 (.050")	38 (15")	64	1	9 ₁	781135	8717574021356
	.325" NK	1,3 (.050")	40 (16")	66	1	1	781136	8717574021363
	.325" NK	1,3 (.050")	45 (18")	72	1	1	781138	8717574021370
	.325" NK	1,3 (.050")	50 (20")	78	1	1	781140	8717574033236
	10	MARIE	7.					