


# 5xD



TiN coated



External Coolant



Straight Shank



Speeds & Feeds  
information pg 359

## Series 651

### General Purpose

HSS, general purpose (Type N), jobber length, 118° point, Form A web thinned >2.36mm dia., standard straight shank, RH helix

Cut / Shank Dia. = h8 tolerance range



Application Materials:



Universal Steels



Cast Iron



General Steels

Diameter (d1)					
Dec. inch	Fract. inch	Wire / letter	mm	l1 mm	l2 mm
0.0079		92	0.200	19.00	2.50
0.0098		87	0.250	19.00	3.00
0.0110		85	0.280	19.00	3.00
0.0118			0.300	19.00	3.00
0.0122		83	0.310	19.00	4.00
0.0130		81	0.330	19.00	4.00
0.0134		80	0.340	19.00	4.00
0.0142			0.360	19.00	4.00
0.0146		79	0.370	19.00	4.00
0.0150			0.380	19.00	4.00

Diameter (d1)					
Dec. inch	Fract. inch	Wire / letter	mm	l1 mm	l2 mm
0.0154			0.390	20.00	5.00
0.0157	1/64		0.400	20.00	5.00
0.0161		78	0.410	20.00	5.00
0.0165			0.420	20.00	5.00
0.0169			0.430	20.00	5.00
0.0173			0.440	20.00	5.00
0.0177			0.450	20.00	5.00
0.0181		77	0.460	20.00	5.00
0.0185			0.470	20.00	5.00
0.0189			0.480	20.00	5.00

Diameter (d1)					
Dec. inch	Fract. inch	Wire / letter	mm	l1 mm	l2 mm
0.0193			0.490	22.00	6.00
0.0197			0.500	22.00	6.00
0.0201		76	0.510	22.00	6.00
0.0205			0.520	22.00	6.00
0.0209		75	0.530	22.00	6.00
0.0213			0.540	24.00	7.00
0.0217			0.550	24.00	7.00
0.0224		74	0.570	24.00	7.00
0.0228			0.580	24.00	7.00
0.0232			0.590	24.00	7.00

To order: Series number + mm, ex. 5518 3.000



