

Технически характеристики

Свредло Milwaukee за метал стандартно 1 мм, 12/34 мм, HSSG с 5% Co, Quad Edge DIN 338

- Metal drill bits ground from solid, extremely heat resistant 5% cobalt-alloyed high speed steel produced according to DIN 338.
- Suitable for drilling high alloy content steels and metals with tensile strengths over 1000 N/mm² like stainless steel.
- QUAD EDGE™ Tip: unique combination of 135° split point and four cutting edges: 135° split point allows for precise & fast drilling start without walking. Four cutting edges create smaller chips to prevent heat build up for longer life.
- Variable flute geometry: For faster material ejection. Helps the bit run cooler and prevent it from burning out faster.
- Enhanced tapered web: Wider core towards the shank of the drill bit. Strengthens the core to increase overall flute durability.

	Article Number	4932373332
.08	Diameter (mm)	1.0
	Pack quantity	10
13V	Total length (mm)	34
10 40	Working length (mm)	12
WW.		
Ma.		

Продукт: Свредло Milwaukee за метал стандартно 1 мм, 12/34 мм, HSSG c 5% Co, Quad Edge DIN 338

Категория: Свредла, райбери, зенкери

Марка: <u>Milwaukee</u> Тип: <u>Свредло Milwaukee</u>