


HSS-G twist drill bit according to DIN 338 ground, left hand cutting



HSS-G

Twist drill bit according to DIN 338 type N, left hand, with straight shank, profile ground, 118° split point

X-Pack: With 10 pcs. up to Ø 10,0,
From Ø 10,2 with 5 pcs. Each

Ø mm	L	L2	Best-Nr. order no.	Ø mm	L	L2	Best-Nr. order no.
1,0	34	12	18 010L	7,0	109	69	18 070L
1,5	40	18	18 015L	7,5	109	69	18 075L
2,0	49	24	18 020L	8,0	117	75	18 080L
2,5	57	30	18 025L	8,5	117	75	18 085L
3,0	61	33	18 030L	9,0	125	81	18 090L
3,2	65	36	18 032L	9,5	125	81	18 095L
3,5	70	39	18 035L	10,0	133	87	18 100L
4,0	75	43	18 040L	10,2	133	87	18 102L
4,2	75	43	18 042L	10,5	133	87	18 105L
4,5	80	47	18 045L	11,0	142	94	18 110L
5,0	86	52	18 050L	11,5	142	94	18 115L
5,5	93	57	18 055L	12,0	151	101	18 120L
6,0	93	57	18 060L	12,5	151	101	18 125L
6,5	101	63	18 065L	13,0	151	101	18 130L
6,8	109	69	18 068L				