


## HSS-G twist drill bit according to DIN 338 ground, left hand cutting



### HSS-G

Twist drill bit according to DIN 338 type N, left hand, with straight shank, profile ground, 118° split point

X-Pack: With 10 pcs. up to Ø 10,0,  
From Ø 10,2 with 5 pcs. Each

Ø mm	L	L2	Best-Nr. order no.	Ø mm	L	L2	Best-Nr. order no.
<b>1,0</b>	34	12	18 010L	<b>7,0</b>	109	69	18 070L
<b>1,5</b>	40	18	18 015L	<b>7,5</b>	109	69	18 075L
<b>2,0</b>	49	24	18 020L	<b>8,0</b>	117	75	18 080L
<b>2,5</b>	57	30	18 025L	<b>8,5</b>	117	75	18 085L
<b>3,0</b>	61	33	18 030L	<b>9,0</b>	125	81	18 090L
<b>3,2</b>	65	36	18 032L	<b>9,5</b>	125	81	18 095L
<b>3,5</b>	70	39	18 035L	<b>10,0</b>	133	87	18 100L
<b>4,0</b>	75	43	18 040L	<b>10,2</b>	133	87	18 102L
<b>4,2</b>	75	43	18 042L	<b>10,5</b>	133	87	18 105L
<b>4,5</b>	80	47	18 045L	<b>11,0</b>	142	94	18 110L
<b>5,0</b>	86	52	18 050L	<b>11,5</b>	142	94	18 115L
<b>5,5</b>	93	57	18 055L	<b>12,0</b>	151	101	18 120L
<b>6,0</b>	93	57	18 060L	<b>12,5</b>	151	101	18 125L
<b>6,5</b>	101	63	18 065L	<b>13,0</b>	151	101	18 130L
<b>6,8</b>	109	69	18 068L				