

## HIGH SPEED STEEL (HSS-R) METAL DRILLS



- STANLEY.**
- General-purpose drills for mild steel and non-ferrous metals
  - Hot rolling high speed cutting steel (HSS), according to DIN 338
  - Cone drill bit – 118° angle

STANLEY	Diameter mm	Length		☒	STANLEY	Diameter mm	Length		☒
		total mm	operating				total mm	operating	
STA50000	1.0	34	12	3	STA50065	6.0	93	57	1
STA50005	1.5	40	18	3	STA50070	6.5	101	63	1
STA50010	2.0	49	24	3	STA50075	7.0	109	69	1
STA50015	2.5	57	30	3	STA50085	8.0	117	75	1
STA50020	3.0	61	33	3	STA50095	9.0	125	81	1
STA50025	3.2	65	36	1	STA50105	10.0	133	87	1
STA50030	3.5	70	39	1	STA50110	11.0	142	94	1
STA50035	4.0	75	43	1	STA50115	12.0	151	101	1
STA50040	4.2	75	43	1	STA50120	13.0	151	101	1
STA50045	4.5	80	47	1	STA50140	10.5	133	87	1
STA50050	4.8	86	52	1	STA50155	14.0	160	108	1
STA50055	5.0	86	52	1	STA50160	15.0	169	114	1
STA50060	5.5	93	57	1	STA50165	16.0	178	120	1

\*reduced grip



Ташев-Галвинг  
www.tashev-galving.com