

**Zubehör,**  
zu PVC-Elektrohren

**Accessories,**  
for electric PVC conduits

**CL, Klemmschelle, anreihbar;** hellgrau (RAL 7035), grau (RAL 7037), schwarz (RAL 9005) oder weiß (RAL 9010), zur Montage mit Dübel DSD oder Schrauben mit Ø 4mm

**CL, clip, interlinkable;** light grey (RAL 7035), grey (RAL 7037), black (RAL 9005) or white (RAL 9010), for mounting with plug DSD or screws with Ø 4mm



Material				Temp.			
PVC-U				-5°C/+60°C *(-25°C/+60°C)			
art	dn	ps	pl	ref			
				hellgrau light grey	grau* grey*	schwarz black	weiß white
CL 16	16,0	100	3200	082 211	082 210	082 212	082 213
CL 20	20,0	100	2400	082 178	082 177	082 179	082 180
CL 25	25,0	100	1600	082 215	082 214	082 216	082 217
CL 32	32,0	100	1600	082 219	082 218	082 220	082 221
CL 40	40,0	50	800	082 223	082 222	082 224	082 225
CL 50	50,0	50	600	082 596	082 595	082 597	082 598
CL 63	63,0	25	300	082 600	082 599	082 601	082 602

**CLB, Haltebügel;** hellgrau (RAL 7035), grau (RAL 7037) oder schwarz (RAL 9005), für Klemmschelle CL

**CLB, bracket;** light grey (RAL 7035), grey (RAL 7037) or black (RAL 9005), for CL clips

**Bestellhinweis:** weiße Ausführung auf Anfrage erhältlich.

**Ordering Note:** white version available upon request.



Material				Temp.		
PVC-U				-5°C/+60°C *(-25°C/+60°C)		
art	dn	ps	pl	ref		
				hellgrau light grey	grau* grey*	schwarz black
CLB 40	40,0	250	8000	023 074	023 071	082 423
CLB 50	50,0	200	6400	023 075	023 072	082 631
CLB 63	63,0	150	4800	023 076	023 073	082 632

**DSD, Steckdübel, halogenfrei;** hellgrau (RAL 7035), für Schnellmontage von Klemmschelle CL, erforderliche Bohrlochgröße Ø 6mm (Gasbeton Ø 5,5mm)

**DSD, plug, halogenfree;** light grey (RAL 7035), for quick and efficient mounting of CL clips, required fixing hole size Ø 6mm (gas concrete Ø 5.5mm)



Material				Temp.	
PA				-25°C/+90°C	
art	ln	ps	pl	ref	
DSD 35	35mm	500	16000	082 226	