

Conduit installation

Single- and double clips

ESS Single fastening clamp

For conduit installation, without wall distance, for example on ceilings and under concrete.

Material halogen-free, PP, UV-stabilised, temperature range: -10 to +85 °C

* IEC / EN 61386-1:2008, IEC / EN 61386-25:2011 tested. HO = halogen-free

Type	Article number	Clamping range mm	Colour	Content Pack/Box
ESS 16–20 HO*	30120	16–20	light grey	200 / 4,400
ESS 20–25 HO*	30140	20–25	light grey	200 / 3,200
ESS 25–32 HO*	30160	25–32	light grey	100 / 2,400
ESS 32–42 HO	30180	32–42	light grey	100 / 1,600



The product for quick installation of conduits onto plaster the ESS single fastening clamp from Schnabl.



DSS Double fastening clamp

For the parallel laying of two conduits without wall distance.

Material halogen-free, PP, UV-stabilised, temperature range: -10 to +85 °C

IEC / EN 61386-1:2008, IEC / EN 61386-25:2011 tested. HO = halogen-free

Type	Article number	Colour	Content Pack/Box
DSS 20–25 HO	30240	light grey	200 / 4,000
DSS 25–32 HO	30250	light grey	100 / 2,400



One borehole is also enough for two conduits – with the double fastening clamp from Schnabl.



DSA Double fastening clamp with spacer

For the parallel laying of two conduits without wall distance; with fixed distance between the conduits.

Material halogen-free, PP, UV-stabilised, temperature range: -10 to +85 °C

IEC / EN 61386-1:2008, IEC / EN 61386-25:2011 tested. HO = halogen-free

Type	Article number	Clamping range mm	Colour	Content Pack/Box
DSA 20–25 HO	30260	20–25	light grey	100 / 2,400
DSA 25–32 HO	30270	25–32	light grey	100 / 1,600



The practical double fastening clamp is also available with a fixed conduit distance.

