

Технически характеристики

The evolution of the K Body REVO



Simply better.

With greater power and safety in a new design



Precise and gentle

Workpieces with sensitive surfaces can be clamped and spread exactly parallel to each other – even behind and on the side of the rail. Corners and recessed edges as well as pointed and round surfaces can also be perfectly aligned:

- due to extremely large clamping surfaces that are attached perpendicular to the rail
- due to three removable pressure caps that are repellent to glue, and also resistant to paint and grease solvents
- due to workpiece supports that prevent the workpiece from coming into contact with the rail



Powerful and safe

They securely clamp with a clamping force of up to 8.000 N:

- due to the metal-reinforced plastic housing
- due to the optimised sliding arm with double slide protection: It holds the clamp reliably with the set clamping force and prevents any unintentional slipping of the sliding arm in the unclamped condition

YouTube 🕨

Versatile and well thought out

The clamps provide an enormous number of possible applications:

- due to ingenious accessories, such as tilting adapter, frame press set, clamp extension and table clamp
- the ergonomically formed 2-component symmetrical plastic handle with hexagon socket means the clamping force can be comfortably applied (max. torque 17 Nm)
- the continuously adjustable head for the KREV Vario version enables the clamp to be positioned in the middle of the workpiece for optimum weight distribution





Технически характеристики

- Clamping force up to 8.000 N
- Very large parallel clamping surfaces with 3 removable pressure caps
- Metal-reinforced plastic housing and optimised sliding arm with double slide protection for more power and safety: The set clamping force is maintained and the sliding arm cannot unintentionally slip in the unclamped condition
- Can be converted without tools for spreading tasks
- High-quality 2-component symmetrical plastic handle with hexagon socket for the comfortable application of the clamping force (max. torque 17 Nm)

-

Y

- KREV with continuously adjustable and fixable upper section for optimum positioning on the workpiece
- Steplessly adjustable and fixable upper section for improved workpiece positioning
- Very large parallel clamping surfaces
- With 2 pressure caps to protect delicate surfaces
- Can be converted to spreading function with no need for tools
- KP Framing System (from 30 cm to 250 cm/12"-98") with four 90° KP Blocks
- Separately adjustable clamping force with 2 inserted clamps per corner
- Lightweight / easy to assemble
- On carded hang pack
- Adapter with tilting clamping jaws with a tilt range of -15° to +15°
- Clamping on sloping and parallel surfaces
- On carded hang pack
- Connect any two K Body parellel clamps to increase the clamping capacity. The connector is made of robust aluminum.
- On carded hang pack
- Especially for DIY applications and domestic appliances
- Special accessory for angle clamps WS 3 / WS 6, screw clamp S 10 and K Body REVO parallel clamps KRE / KREV and KR / KRV to hold them to a work surface edge

	KE and	d Vario	o K Body RI	EVO KRE	V		
Order- No.	←a→	←b→	< e →	←X→	۵'۵	Ø	
	mm	mm	mm	mm	kg	qty.	V3
KRE30-2K	300	95	255-390	29 x 9	2.15	2	
KRE60-2K	600	95	255-730	29 x 9	2.76	2	
KRE80-2K	800	95	255-930	29 x 9	3.10	2	
KRE100-2K	1000	95	255-1130	29 x 9	3.45	2	-
	1250	95	255-1355	29 x 9	3.87	2	-
	1500	95	255-1610	29 x 9	4.28	2	-
KRE200-2K	2000	95	255-2080	29 x 9	5.09	2	
	2500	95	255-2580	29 x 9	6.05	2	-
	1000	95	260-1130	29 x 9	3.77	2	
	1500	95	260-1130	29 x 9	4.25	2	
	2000	95	260-2080	29 x 9	5.30	2	
	2500	95	260-2580	29 x 9	6.30	2	-
a	2000	35	200-2580 e	23 2 3	0.50	2	
				BO			
				Hall	X		
	<u></u>	-12					
Variable jaw K							
	NE-VU	0					
Order- No.		Suit	able or		52	Ø	
110.							1/2
	KDE				kg	qty.	V3
KRE-VO	KRE /	KREV	/ KR / KRV	L L	0.59	12	
				C	\mathcal{O}	r	
Framing set KF	2						
Order-		Suit	able		1	-	
No.			or		5	Ø	
					kg	qty.	V3
КР	KRE	(KREV	/ KR / KRV	().55	12	
						12	
Contents: 4 rail	coupli	ngs ar	nd 4 adapte	rs			
Tilting K Body	clamn	adant	er KR-AS (2 pcs /h	ag)		
	oramp			- poo./ u	-9/		
Order-	Suitable for				42	Ø	
No.		fo	Dr				
					kg	qty.	V3
KR-AS	KRE /	′ KREV	/ KR / KRV	().18	12	
K Body Extend	er KBX						
Order-		Suit	able		52	A	
No.		fo	or		50	Ø	
					kg	qty.	V3
KBX20	KRE /	KREV	/ KR / KRV	().75	12	
Table clamp TK	(6						
		.	ahla				
Owders			able or		52	Ø	
Order- No							
Order- No.			,,		1		
	1/==		/ KR / KRV		kg).10	qty. 50	V3