

# Plunge-cut saw TS 55 FEBQ-Plus-FS

Item number 577010



Power consumption
<b>1 200 W</b>
Idle engine speed
<b>2 000 - 5 800 min<sup>-1</sup></b>
Saw blade diameter
<b>160.00 mm</b>
Angular range
<b>-1 - 47 °</b>
Cutting depth
<b>0 - 55 mm</b>
Cutting depth 45°
<b>43 mm</b>
Dust extraction connection dia.
<b>27/36 mm</b>
Weight
<b>4.50 kg</b>

**Antistatic function**

Mobile dust extractors and tools with the antistatic function to prevent static charge from accumulating when working.

**MMC Multi Material Control electronics**

“Multi Material Control” power electronics with constant adjustable speed and temperature monitor for work on all types of material.

**Splinter guard**

Patented splinterguard for splinter-free cuts on both sides when sawing.

**FastFix**

Makes changing routing, sawing, planing, sanding, drilling and screwdriving tools easier.

**Guide system**

Patented guide system for safe guidance of saws and router bits.

**CLEANTEC**

Integrated bayonet fitting as the connecting element between the extractor and the tool.

**Plug it**

Removable, replaceable mains cable with safety lock for quick conversion.

**Quick-acting brake**

For safe work when planing, sawing and routing.

Sawing wood: Total vibration average, Ah
<b>2.50 m/s<sup>2</sup></b>
Sawing wood: A-weighted sound pressure level, LpA
<b>90.00 dB(A)</b>
Sawing wood: Uncertainty (noise) K
<b>3.00 dB</b>
Sawing wood: A-weighted sound power level, LWA
<b>101.00 dB(A)</b>

Sawing wood: Standards series EN
<b>62841</b>
Sawing wood: Uncertainty (vibration) K
<b>1.50 m/s<sup>2</sup></b>
Sawing metal: A-weighted sound pressure level, LpA
<b>90.00 dB(A)</b>
Sawing metal: Total vibration average, Ah
<b>2.50 m/s<sup>2</sup></b>
Sawing metal: Uncertainty (vibration) K
<b>1.50 m/s<sup>2</sup></b>
Sawing metal: A-weighted sound power level, LWA
<b>101.00 dB(A)</b>
Sawing metal: Standards series EN
<b>62841</b>
Sawing metal: Uncertainty (noise) K
<b>3.00 dB</b>

Ташев-Галвинг ООД  
[www.tashev-galving.com](http://www.tashev-galving.com)