

Slide Compound Miter Saw

305mm(12") C 12RSH2



Improved Work Efficiency

with the Compact Slide System & Wide Base



Improved Work Efficiency with the Compact Slide System & Wide Base





features a fixed rail slide design that eliminates the need for rear clearance to accommodate the extension of the sliding rails. This system allows the saw to sit up against a wall or to be placed in tight work areas without compromising cutting capacity.



Saw blade diameter 290 - 305mm





high enough to support large work pieces for



7 kg* 2kg lighter
than the previous model C12RSH

*Without the cord.

SPECIFICATIONS

| SPECIFICATIO | NO | | | |
|----------------------------|---|---|--|--|
| C 12KSH2 | | | | |
| | Blade Dia. | 305mm (12") | | |
| Capacity | Cross Cut 0° (H x W) | 105 x 312mm (4-1/8 x 12-1/4") | | |
| | Miter Left/Right 45° (H x W) | 105 x 220mm (4-1/8 x 8-5/8") | | |
| | Bevel Left 45° (H x W) | 68 x 312mm (2-5/8 x 12-1/4") | | |
| | Bevel Right 45° (H x W) | 43 x 312mm (1-11/16 x 12-1/4") | | |
| | Bevel (Left) 45° + Miter (Left) 45° (H x W) | 68 x 220mm (2-5/8 x 8-5/8") | | |
| | Bevel (Left) 45° + Miter (Right) 31° (H x W) | 68 x 265mm (2-5/8 x 10-7/16") | | |
| | Bevel (Right) 45° + Miter (Right) 45° (H x W) | 43 x 220mm (1-11/16 x 8-5/8") | | |
| | Bevel (Right) 45° + Miter (Left) 31° (H x W) | 43 x 265mm (1-11/16 x 10-7/16") | | |
| Power Input | | 1,520W | | |
| No Load Speed | | 4,000/min. | | |
| Miter Angle | | Right: 0-57° Left: 0-45° | | |
| Bevel Angle | | Right: 0-45° Left: 0-45° | | |
| Positive Miter Angle Stops | | 0, 15, 22.5, 31.6 and 45° | | |
| Dimensions | | 655 x 890 x 724mm (25-25/32 x 35-3/64 x 28-1/2") | | |
| Weight | | 27kg (59.5lbs.) without the cord | | |
| Standard Accessories | | Blade, Dust Bag, Vise Ass'y, Box Wrench, Holder | | |

| Distributed by: | |
|-----------------|--|
| | |
| | |
| | |
| | |
| | |

Hitachi Koki Co., Ltd.

www.hitachi-koki.com