



- Up to 375 cuts per charge in 2X4 SPF when using BSL36B18 battery*1
- Accepts ET36A AC/DC Adapter for continuous operation
- Compact slide system
- Laser Marker: Guide system on cut line
- LED light

	Blade Dia.	255mm (10")
	0°(Right Angle)	with anchor plate 89 x 292mm (3-1/2" x 11-1/2") without anchor plate 64 x 318mm (2-1/2" x 12-1/2")
	Miter Left/Right 45°	with anchor plate 89 x 204mm (3-1/2" x 8") without anchor plate 64 x 222mm (2-1/2" x 8-3/4")
	Bevel Left 45°	with anchor plate 45 x 292mm (1-3/4" x 11-1/2") without anchor plate 41 x 318mm (1-5/8" x 12-1/2")
Capacity (H x W)	Bevel Right 45°	with anchor plate 25 x 292mm (1" x 11-1/2") without anchor plate 19 x 318mm (3/4" x 12-1/2")
	Miter Left/Right 45° + Bevel Left 45°	with anchor plate 45 x 204mm (1-3/4" x 8") without anchor plate 41 x 222mm (1-5/8" x 8-3/4")
	Miter Left/Right 45° + Bevel Right 45°	with anchor plate 25 x 204mm (1" x 8") without anchor plate 19 x 222mm (3/4" x 8-3/4")
	Voltage	36V
	No Load Speed	4,000/min
	Miter Angle	Right 0 – 60°

	Left	0 – 55°
Bevel Angle	Right	0 – 48°
	Left	0 – 48°
Positive Miter Angle Stop		0, Right and Left 15°, 22.5°, 31.6°, 45°
Dimensions		778 x 792 x 686mm (30-5/8" x 31-3/16" x 27")
Weight*2		20.6kg (45.5lbs.) with BSL36B18

Ташев-Галвинг ООД
www.tashev-galving.com