

## Акумулаторен настолен циркуляр



### LS002GZ01

Напрежение:	40 V max XGT
Капацитет на батерията:	2,0 / 2,5 / 4,0 / 5,0 / 8,0Ah
Вид на батерията:	Li-ion
Обороти на празен ход:	4.800min <sup>-1</sup>
Диаметър на диска Ø:	216mm
Размер на вътр.отвор:	30mm
Рязане под ъгъл л/д:	48 - 48°
Макс. ъгъл на герунг л/д:	60 - 60°
Рязане при 0°:	70 x 312mm
Рязане при 45°:	70 x 220mm
Шум: звуково налягане:	89,0dB(A)
Шум: звукова мощност:	100,0dB(A)
Шум: отклонение:	3,0dB(A)
Вибрации: рязане:	2,5m/s <sup>2</sup>
Вибрации: отклонение (K):	1,5m/s <sup>2</sup>
Размери (Д x Ш x В):	702 x 551 x 557mm
Тегло (ЕПТА):	17,0kg



**BL MOTOR** **AWS** **DXT**  
Deep and Exact Cutting Technology

- Excellent performance in continuous heavy duty applications
- High precision cutting - integrated structure of Alu guide fence and lower fence increases rigidity to provide a stable work piece support
- Motor head slides on fixed pipes without extending the machine's rear end
- LED light casts a shadow of the blade onto the workpiece as an exact cutting line.
- Dual dust collection ports and redesigned blade case for efficient dust extraction
- Possible use of AWS system