Chainsaws

HUSQVARNA 120 Mark II

Easy to use, all-round chainsaw for homeowners. Thanks to sufficient cutting performance the saw makes light work of cutting firewood, light felling or limbing. Features X-Torq® engine technology for low emissions and Air Injection that keeps the filter clean. Low kickback cutting equipment for increased safety.

Cylinder displacement

38.2 cm³

■ Weight (excl. cutting equipment) 4.85 kg



Rec. retail price inc. VAT



Tolling to the state of the sta

1 of 3 3/27/2019, 3:09 PM

FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its design and features.



Air Injection

Centrifugal air cleaning system for reduced wear and longer operating time between filter cleanings.



X-Torq®

Deliver lower fuel consumption and reduced exhaust emission levels in accordance with the world's most stringent environmental regulations.

Combined choke/stop control

Combined choke/stop control allow for easier starting and reduce the risk of engine flooding.



LowVib®

Effective anti-vibration dampeners absorb vibration, sparing the user's arms and hands.

Fuel pump

3/27/2019, 3:09 PM 2 of 3

Specifications



1.4 kW Power output 38.2 cm³ Cylinder displacement 9000 rpm Maximum power speed 3000 rpm Idling speed Clutch engagement speed (±120) 4250 rpm **Champion RCJ7Y** Spark plug 0.5 mm Electrode gap 0.25 mm Ignition module air gap **Automatic** Oil pump type



18 in Recommended bar length, max 14 in Recommended bar length, min Chain speed at max power 16.8 m/s Chain speed at 133% of maximum engine power 22.3 m/s



Dimensions

Weight (excl. cutting equipment)

Lubricant

Oil tank volume 0.21

Oil pump type **Automatic**



Sound power level, guaranteed (LWA) Sound power level, measured A OHINA OS Sound pressure level at operators ear

113 dB(A)

4.85 kg

100.7 dB(A)

((())) Vibration

Equivalent vibration level (ahv, eq) front handle 2.1 m/s² Equivalent vibration level (ahv, eq) rear handle 2.7 m/s²

3 of 3 3/27/2019, 3:09 PM