

Трион верижен бензинов 550 XP MARK II



- Мощен, издръжлив и лесен за маневриране, 50 кубиков трион с отлична производителност и капацитет на рязане. Подходящ за изсичане, накланяне и изкореняване на малки и средни дървета. Олекотеният дизайн и множество иновативни функции осигуряват ефективна, надеждна и удобна работа.

Engine

Power output	3.0 kW
Cylinder displacement	50.1 cm ³
Maximum power speed	10200 rpm
Idle speed	2800 rpm
Torque, max.	3.15 Nm
Torque, max. at rpm	2800 rpm
Clutch engagement speed (±120)	3900 rpm
Fuel consumption	432 g/kWh
Fuel consumption	1.3 kg/h
Spark plug	NGK CMR6H
Electrode gap	0.5 mm
Ignition module air gap	0.3 mm
Oil pump type	Adjustable flow, no flow at idle
Exhaust emissions (CO2 EU V)	813 g/kWh

Dimensions

Weight (excl. cutting equipment)	3.3 kg
----------------------------------	--------

Sound and Noise

Sound power level, guaranteed (LWA)	117 dB(A)
Sound power level, measured	115 dB(A)
Sound pressure level at operators ear	107 dB(A)

Equipment

Bar length (incl. sprocket)	18"
Chain type	SP33G
Sprocket type	Rim 7
Bar mount type	Small
Recommended bar length, min-max	13-20 in

Lubricant

Lubricant type	Husqvarna 2 stroke or equiv. at 50:1
Oil tank volume	0.32 l

Vibration

Equivalent vibration level (ahv, eq) front handle	3.3 m/s ²
Equivalent vibration level (ahv, eq) rear handle	4.9 m/s ²