

Индустриални маркучи за вентилация

// 178AA



Air ducting - High temperature +120 °C (+248 °F)

Construction: black EPDM/PP fully recyclable and halogens/ phthalates free.

Reinforcement: steel helix wire.

Application: hot air, gas, fumes extraction-ventilation where high temperature resistance is required.

Constant operation: -40 °C +120 °C (-40 °F +248 °F)

| ↔ | | ↔ | | ↙ | | ↘ | | ⌒ | | ⌒ | | |
|-------|---------|----|----|-----|-----|-----|-----|-------|-------|---|-------|-------|
| mm | in | mm | in | bar | psi | bar | psi | mm | in | % | kg/m | lb/ft |
| 40,0 | 1 9/16" | | | | | | | 32,0 | 1,26 | | 0,200 | 0,14 |
| 51,0 | 2" | | | | | | | 40,0 | 1,57 | | 0,250 | 0,17 |
| 63,0 | 2 1/2" | | | | | | | 55,0 | 2,17 | | 0,310 | 0,21 |
| 70,0 | 2 3/4" | | | | | | | 60,0 | 2,36 | | 0,440 | 0,30 |
| 76,0 | 3" | | | | | | | 65,0 | 2,56 | | 0,460 | 0,31 |
| 80,0 | 3 1/8" | | | | | | | 65,0 | 2,56 | | 0,500 | 0,34 |
| 90,0 | 3 1/2" | | | | | | | 75,0 | 2,95 | | 0,580 | 0,39 |
| 102,0 | 4" | | | | | | | 85,0 | 3,35 | | 0,610 | 0,41 |
| 110,0 | 4 5/16" | | | | | | | 90,0 | 3,54 | | 0,660 | 0,45 |
| 120,0 | 4 3/4" | | | | | | | 100,0 | 3,94 | | 0,720 | 0,49 |
| 127,0 | 5" | | | | | | | 105,0 | 4,13 | | 0,830 | 0,56 |
| 140,0 | 5 1/2" | | | | | | | 115,0 | 4,53 | | 0,940 | 0,64 |
| 152,0 | 6" | | | | | | | 125,0 | 4,92 | | 1,010 | 0,68 |
| 160,0 | 6 5/16" | | | | | | | 130,0 | 5,12 | | 1,090 | 0,74 |
| 180,0 | 7 1/16" | | | | | | | 150,0 | 5,91 | | 1,330 | 0,90 |
| 203,0 | 8" | | | | | | | 165,0 | 6,50 | | 1,480 | 1,00 |
| 254,0 | 10" | | | | | | | 210,0 | 8,27 | | 1,930 | 1,30 |
| 305,0 | 12" | | | | | | | 250,0 | 9,84 | | 2,380 | 1,60 |
| 355,0 | 14" | | | | | | | 300,0 | 11,81 | | 2,770 | 1,87 |
| 406,0 | 16" | | | | | | | 350,0 | 13,78 | | 3,210 | 2,16 |