

Flexible Schutzschläuche,
halogenfreier Kunststoff

Flexible Protective Conduits,
Halogenfree Synthetic Material

MFXE, flexibler Kabelschutzschlauch aus Polyethylen, leicht, gewellt; schwarz (RAL 9005, UV-stabilisiert), in Ringen zu 100m

MFXE, flexible protective conduit from polyethylene, light gauge, corrugated; black (RAL 9005, UV stabilised), in coils of 100m



Material	Mechan.	UV stabil.	Temp.	
PE	> 320 N	<input checked="" type="checkbox"/>	-40°C/+100°C	
art	dn	di	ps [m]	ref
MFXE 1	7,0	5,2	100	026 328
MFXE 2	9,8	7,2	100	026 329
MFXE 3	11,4	8,5	100	026 330

MFXP, flexibler Kabelschutzschlauch aus Polypropylen, leicht, gewellt; schwarz (RAL 9005, UV-stabilisiert), in Ringen zu 100m

MFXP, flexible protective conduit from polypropylene, light gauge, corrugated; black (RAL 9005, UV stabilised), in coils of 100m



Material	Mechan.	UV stabil.	Temp.	
PP	> 320 N	<input checked="" type="checkbox"/>	-40°C/+130°C	
art	dn	di	ps [m]	ref
MFXP 1	7,0	5,2	100	035 505
MFXP 2	9,8	7,2	100	035 506
MFXP 3	11,4	8,5	100	035 507