

Data sheet

Part No. **SGL S BK UV**


Description straight gland
for corrugated conduits, with patented plug-in system for quick-fit assembly, pull-tight connection and jetting water tight sealings, with metric thread according to EN 60423

Colour black, similar to RAL 9005

Fire Behaviour non flame propagating

Classification IP65

Standard: EN 61386-1, EN 61386-23, EN 60754



Working temperature
-25 to +105 °C

Degree of protection (IP)
IP65

UV stabilized
true – up to 10 years

Art. No.	Nominal diameter	Thread	Thread length	Total length	PU	PU
043067	12 mm	M12 x 1.5	8 mm	18,3 mm	100 pc	3200 pc
043068	16 mm	M16 x 1.5	10,5 mm	18,9 mm	100 pc	1600 pc
043069	20 mm	M20 x 1.5	12 mm	24 mm	50 pc	1200 pc
043070	25 mm	M25 x 1.5	15 mm	30,4 mm	50 pc	400 pc
043071	32 mm	M32 x 1.5	15 mm	32 mm	30 pc	360 pc
043073	40 mm	M40 x 1.5	15 mm	38 mm	20 pc	240 pc
043074	50 mm	M50 x 1.5	15 mm	42,4 mm	16 pc	128 pc
043077	63 mm	M63 x 1.5	20 mm	54 mm	8 pc	64 pc

Further technical details

Details

Model	Straight
Revolving thread	False
Construction type	External thread
Material	PA-Blend

Cardboard packaging used is made from 100% waste paper and is fully recyclable, plastic packaging is fully recyclable.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.