

Data sheet

Part No.	SLN BK UV
Description	lock nut, halogen-free for fixing of conduit glands, with metric thread according to EN 60423
Colour	black, similar to RAL 9005
Fire Behaviour	non flame propagating
Usage	IP65 when using in combination with gland types SGL S, SEG S and SFL S



Standard: EN 61386-1, EN 61386-23, EN 60754



Working temperature
-25 to +105 °C

UV stabilized
true – up to 10 years

Art. No.	Item code	Nominal thread size	PU	PU
082004	SLN 12 BK UV	M 12 x 1,5	100 pc	-
026257	SLN 16 BK UV	M 16 x 1,5	200 pc	8000 pc
026256	SLN 20 BK UV	M 20 x 1,5	200 pc	6400 pc
026255	SLN 25 BK UV	M 25 x 1,5	100 pc	4000 pc
026254	SLN 32 BK UV	M 32 x 1,5	100 pc	2400 pc
026053	SLN 40 BK UV	M 40 x 1,5	30 pc	1200 pc
026054	SLN 50 BK UV	M 50 x 1,5	25 pc	1000 pc
027590	SLN 63 BK UV	M 63 x 1,5	20 pc	480 pc

Further technical details

Details	
Thread type	Metric
Pitch thread	1,5 mm
Shape	Hexagonal
Halogen free	True
Material	PA-Blend