

AFT/MBS, Rohranschluss mit Innengewinde;
hellgrau (RAL 7035), grau (RAL 7037), schwarz (RAL 9005) oder
weiß (RAL 9010), zum Anschluss von starren oder biegsamen
Rohren an Abzweig- und Panzerkästen



Material				Temp.			
PVC-U				-5°C/+60°C *(-25°C/+60°C)			
art	dn	ps	pl	ref			
				hellgrau light grey	grau* grey*	schwarz black	weiß white
AFT/MBS 16	16,0	100	2400	020 754	020 783	009 085	010 183
AFT/MBS 20	20,0	100	1200	020 755	020 784	009 086	010 184
AFT/MBS 25	25,0	50	600	020 756	020 785	009 087	010 185
AFT/MBS 32	32,0	20	480	020 757	020 786	009 088	010 186
AFT/MBS 40	40,0	25	300	020 758	020 787	009 089	010 187
AFT/MBS 50	50,0	10	120	020 759	020 788	009 090	010 188

AMT/LR, Rohranschluss mit Gewinding; hell-
grau (RAL 7035), grau (RAL 7037), schwarz (RAL 9005) oder
weiß (RAL 9010), zum Anschluss von starren oder biegsamen
Rohren an Abzweig- und Panzerkästen



Material				Temp.			
PVC-U				-5°C/+60°C *(-25°C/+60°C)			
art	dn	ps	pl	ref			
				hellgrau light grey	grau* grey*	schwarz black	weiß white
AMT/LR 20	20,0	100	1200	009 574	020 790	009 548	009 600
AMT/LR 25	25,0	50	600	009 575	020 791	009 549	009 601

AMT/LN, Rohranschluss mit Gewindemutter;
hellgrau (RAL 7035), grau (RAL 7037) oder schwarz (RAL 9005),
zum Anschluss von starren oder biegsamen Rohren an
Abzweig- und Panzerkästen



Material				Temp.			
PVC-U				-5°C/+60°C *(-25°C/+60°C)			
art	dn	ps	pl	ref			
				hellgrau light grey	grau* grey*	schwarz black	
AMT/LN 20	20,0	100	1200	009 579	020 792	009 553	
AMT/LN 25	25,0	50	600	009 580	020 793	009 554	

**AFT/MBS, adaptor with female thread and male
bush;** light grey (RAL 7035), grey (RAL 7037), black (RAL 9005) or
white (RAL 9010), for the connection of rigid or pliable conduits
with distribution and enclosure boxes

AMT/LR, adaptor with male thread and lock ring;
light grey (RAL 7035), grey (RAL 7037), black (RAL 9005) or
white (RAL 9010), for the connection of rigid or pliable conduits
with distribution and enclosure boxes

AMT/LN, adaptor with male thread and lock nut;
light grey (RAL 7035), grey (RAL 7037) or black (RAL 9005), for
the connection of rigid or pliable conduits with distribution and
enclosure boxes