

**Фрезер Alfa за метал за магнитна бормашина удължен ф
16x50 мм**



Ташев-Галвинг ООД
www.tashev-galving.com



ALFRA ROTABEST® - HSS-Co-Eco CUTTERS

With 19.0 mm Weldon shank

- With 19.0 mm Weldon shank, 2 clamping surfaces, 1 counterbore for RotaQuick®
- Internal bore 6.35 mm
- Steel quality: Special high-capacity speed steel, cobalt
- Polished section: with pre- and post-cutting




Suitable for:
ALFRA-Rotabest® (Weldon), ALFRA-RotaQuick® quick-change system, BDS, Bux, Ruko, Magnetor, Euroboor, Universal, Nitto, Jancy, Hougen, Magtron, Promac, Rotabroach and all other magnetic drilling machines with Weldon shank.

| Ø in mm Cutting depth | Prod.-No. 25 mm | Prod.-No. 35 mm | Prod.-No. 50 mm | Prod.-No.* 110 mm |
|--------------------------|--------------------|--------------------|--------------------|----------------------|
| 12.0 | 1901012025 | 1901012035 | 1901012050 | - |
| 13.0 | 1901013025 | 1901013035 | 1901013050 | - |
| 13.5 | 1901013525 | - | 1901013550 | - |
| 14.0 | 1901014025 | 1901014035 | 1901014050 | - |
| 15.0 | 1901015025 | 1901015035 | 1901015050 | - |
| 15.5 | 1901015525 | - | 1901015550 | - |
| 16.0 | 1901016025 | 1901016035 | 1901016050 | - |
| 17.0 | 1901017025 | 1901017035 | 1901017050 | - |
| 17.5 | 1901017525 | - | 1901017550 | - |
| 18.0 | 1901018025 | 1901018035 | 1901018050 | - |
| 19.0 | 1901019025 | 1901019035 | 1901019050 | - |
| 19.5 | 1901019525 | - | 1901019550 | - |
| 20.0 | 1901020025 | 1901020035 | 1901020050 | 1901020110 |
| 21.0 | 1901021025 | 1901021035 | 1901021050 | - |
| 22.0 | 1901022025 | 1901022035 | 1901022050 | 1901022110 |
| 23.0 | 1901023025 | 1901023035 | 1901023050 | - |
| 24.0 | 1901024025 | 1901024035 | 1901024050 | 1901024110 |
| 25.0 | 1901025025 | 1901025035 | 1901025050 | 1901025110 |
| 26.0 | 1901026025 | 1901026035 | 1901026050 | 1901026110 |
| 26.5 | 1901026525 | - | 1901026550 | - |
| 27.0 | 1901027025 | 1901027035 | 1901027050 | - |
| 28.0 | 1901028025 | 1901028035 | 1901028050 | 1901028110 |
| 29.0 | 1901029025 | 1901029035 | 1901029050 | - |
| 30.0 | 1901030025 | 1901030035 | 1901030050 | 1901030110 |
| 31.0 | 1901031025 | 1901031035 | 1901031050 | - |
| 32.0 | 1901032025 | 1901032035 | 1901032050 | 1901032110 |
| 33.0 | 1901033025 | 1901033035 | 1901033050 | - |
| 34.0 | 1901034025 | 1901034035 | 1901034050 | - |
| 35.0 | 1901035025 | 1901035035 | 1901035050 | 1901035110 |
| 36.0 | 1901036025 | 1901036035 | 1901036050 | - |
| 37.0 | 1901037025 | 1901037035 | 1901037050 | - |
| 38.0 | 1901038025 | 1901038035 | 1901038050 | - |
| 39.0 | 1901039025 | 1901039035 | 1901039050 | - |
| 40.0 | 1901040025 | 1901040035 | 1901040050 | 1901040110 |
| 41.0 | 1901041025 | - | 1901041050 | - |
| 42.0 | 1901042025 | - | 1901042050 | - |
| 43.0 | 1901043025 | - | 1901043050 | - |
| 44.0 | 1901044025 | - | 1901044050 | - |
| 45.0 | 1901045025 | - | 1901045050 | 1901045110 |
| 46.0 | 1901046025 | - | 1901046050 | - |
| 47.0 | 1901047025 | - | 1901047050 | - |
| 48.0 | 1901048025 | - | 1901048050 | - |
| 49.0 | 1901049025 | - | 1901049050 | - |
| 50.0 | 1901050025 | - | 1901050050 | 1901050110 |
| 51.0 | - | - | 1901051050 | - |
| 52.0 | 1901052025 | - | 1901052050 | - |
| 53.0 | - | - | 1901053050 | - |
| 54.0 | - | - | 1901054050 | - |
| 55.0 | 1901055025 | - | 1901055050 | - |
| 56.0 | - | - | 1901056050 | - |
| 57.0 | - | - | 1901057050 | - |
| 58.0 | - | - | 1901058050 | - |
| 59.0 | - | - | 1901059050 | - |
| 60.0 | 1901060025 | - | 1901060050 | - |
| Ejector pin | 1926500 | 1935500 | 1950500 | 2001502 |
| Dimensions | 6.35 x 77 | 6.35 x 87 | 6.35 x 102 | 8 x 160 |

* Important: HSS-Co-Eco cutters with a cutting depth of 110 mm can now be used with AMT 2 L (Prod.-No. 18003 L) or AMT 3 L (Prod.-No. 18025 L) tool holders.



Counterbore for RotaQuick® Weldon



High-performance tooting with pre- (1) and post-cutting (2)



Продукт: [Фрезер Alfa за метал за магнитна бормашина удължен ф 16x50 мм](#)
 Категория: [Консумативи за фрези и оберфрези](#)
 Бранд: [Alfra](#)
 Категория бранд: [Фрезер Alfa](#)