

**Фрезер Osawa за метал челно-цилиндричен двупер ф
12x16/73 мм, ф 12 мм, End mills WS2**



n **Vf**
PAGE
263-266

DIN
327

WS2 - TAWS2 - WSB2 - TAWSB2 (e8)						
Ø mm	1-3	3.5-6	6.5-10	10.5-18	19-30	32-40
tol. D µ	-14 / -28	-20 / -38	-25 / -47	-32 / -59	-40 / -73	-50 / -89
tol. R µ	±20					



WS2
TAWS2

WSB2
TAWSB2


Z2	Z2	Z2 BALL	Z2 BALL
HSS/Co	HSS/Co	HSS/Co	HSS/Co
BR	P1200	P1200	P1200
		BALL NOSE	BALL NOSE

				30°	30°	30°	30°
				Stock	Stock	Stock	Stock
D(e8)	d(h6)	I	L				
mm 1	6	2.5	47	h	h		
1.5	6	3	47	h	h		
2	6	4	48	h	h	h	f
2.5	6	5	49	h	h	f	f
3	6	5	49	h	h	h	h
3.5	6	6	50	h	h	f	f
4	6	7	51	h	h	h	h
4.5	6	7	51	h	h	f	f
5	6	8	52	h	h	h	h
5.5	6	8	52	h	h	f	f
6	6	8	52	h	h	h	h
6.5	10	10	60	h	h		
7	10	10	60	h	h	f	f
7.5	10	10	60	h	h		
8	10	11	61	h	h	h	h
8.5	10	11	61	h	h		
9	10	11	61	h	h	f	f
9.5	10	11	61	h	h		
10	10	13	63	h	h	h	h
10.5	12	13	70	h	h		
11	12	13	70	h	h	f	f
11.5	12	13	70	h	h		
12	12	16	73	h	h	h	h
12.5	12	16	73	h	h		
13	12	16	73	h	h	f	f
13.5	12	16	73	h	h		
14	12	16	73	h	h	h	h
15	12	16	73	h	h	f	f
16	16	19	79	h	h	h	h
17	16	19	79	h	h	f	f
18	16	19	79	h	h	h	h
19	16	19	79	h	h	f	f
20	20	22	88	h	h	h	h
21	20	22	88	f	h		
22	20	22	88	h		h	f
24	25	26	102	h	f		

h stock standard f non-standard stock EX stock exhaustion

n Vf
PAGE 263-266
DIN 327

WS2 - TAWS2	WSB2 - TAWSB2 (e8)	3.5-6	6.5-10	10.5-18	19-30	32-40
tol. D μ	-14 / -28	-20 / -38	-25 / -47	-32 / -59	-40 / -73	-50 / -89
tol. R μ			±20			



WS2	d	L		I	D				
TAWS2	—	L		I	D				
WSB2	d	L		I	D				
TAWSB2	—	L		I	D				
						HSS/Co	HSS/Co	HSS/Co	HSS/Co
						N	N	N BALL NOSE	BALL NOSE
						30°	30°	30°	30°
D(e8)	d(h6)	I	L	Stock	Stock	Stock	Stock		
mm 25	25	26	102	h	h	h	f		
26	25	26	102	h					
27	25	26	102	f					
28	25	26	102	h		f	f		
30	25	26	102	h		f	f		
32	32	32	112	f					

h stock standard f non-standard stock EX stock exhaustion

Продукт: [Фрезер Osawa за метал челно-цилиндричен двупер ф 12x16/73 мм, ф 12 мм, End mills WS2](#)

Категория: [Консумативи за фрези и обертфрези](#)

Бранд: [Osawa](#)

Категория бранд: [Фрезер Osawa](#)