



ALFRA ROTABEST® – HSS-Co-Eco CUTTERS

With 19.0 mm Weldon shank

Dimensions in
inches available
upon request

- With 19.0 mm Weldon shank,
2 clamping surfaces, 1 counterbore for RotaQuick®
- Internal bore 6.35 mm
- Steel quality: Special high-capacity speed steel, cobalt
- Polished section: with pre- and post-cutting

Suitable for:

ALFRA-Rotabest® (Weldon), ALFRA-RotaQuick® quick-change system, BDS, Bux, Ruko, Magnetor, Euroboor, Universal, Nitto, Jancy, Hougen, Magtron, Promac, Rotabroach and all other magnetic drilling machines with Weldon shank.

Ø in mm	Prod.-No.	Prod.-No.	Prod.-No.	Prod.-No.*
Cutting depth	25 mm	35 mm	50 mm	110 mm
12.0	1901012025	1901012035	1901012050	–
13.0	1901013025	1901013035	1901013050	–
13.5	1901013525	–	1901013550	–
14.0	1901014025	1901014035	1901014050	–
15.0	1901015025	1901015035	1901015050	–
15.5	1901015525	–	1901015550	–
16.0	1901016025	1901016035	1901016050	–
17.0	1901017025	1901017035	1901017050	–
17.5	1901017525	–	1901017550	–
18.0	1901018025	1901018035	1901018050	–
19.0	1901019025	1901019035	1901019050	–
19.5	1901019525	–	1901019550	–
20.0	1901020025	1901020035	1901020050	1901020110
21.0	1901021025	1901021035	1901021050	–
22.0	1901022025	1901022035	1901022050	1901022110
23.0	1901023025	1901023035	1901023050	–
24.0	1901024025	1901024035	1901024050	1901024110
25.0	1901025025	1901025035	1901025050	1901025110
26.0	1901026025	1901026035	1901026050	1901026110
26.5	1901026525	–	1901026550	–
27.0	1901027025	1901027035	1901027050	–
28.0	1901028025	1901028035	1901028050	1901028110
29.0	1901029025	1901029035	1901029050	–
30.0	1901030025	1901030035	1901030050	1901030110
31.0	1901031025	1901031035	1901031050	–
32.0	1901032025	1901032035	1901032050	1901032110
33.0	1901033025	1901033035	1901033050	–
34.0	1901034025	1901034035	1901034050	–
35.0	1901035025	1901035035	1901035050	1901035110
36.0	1901036025	1901036035	1901036050	–
37.0	1901037025	1901037035	1901037050	–
38.0	1901038025	1901038035	1901038050	–
39.0	1901039025	1901039035	1901039050	–
40.0	1901040025	1901040035	1901040050	1901040110
41.0	1901041025	–	1901041050	–
42.0	1901042025	–	1901042050	–
43.0	1901043025	–	1901043050	–
44.0	1901044025	–	1901044050	–
45.0	1901045025	–	1901045050	1901045110
46.0	1901046025	–	1901046050	–
47.0	1901047025	–	1901047050	–
48.0	1901048025	–	1901048050	–
49.0	1901049025	–	1901049050	–
50.0	1901050025	–	1901050050	1901050110
51.0	–	–	1901051050	–
52.0	1901052025	–	1901052050	–
53.0	–	–	1901053050	–
54.0	–	–	1901054050	–
55.0	1901055025	–	1901055050	–
56.0	–	–	1901056050	–
57.0	–	–	1901057050	–
58.0	–	–	1901058050	–
59.0	–	–	1901059050	–
60.0	1901060025	–	1901060050	–

Ejector pin	1926500	1935500	1950500	2001502
Dimensions	6.35 x 77	6.35 x 87	6.35 x 102	8 x 160



Counterbore for RotaQuick® Weldon



High-performance toothings with pre- (1) and post-cutting (2)



* Important: HSS-Co-Eco cutters with a cutting depth of 110 mm can now be used with AMT 2 L (Prod.-No. 18003 L) or AMT 3 L (Prod.-No. 18025 L) tool holders.