

Wilo-DrainLift MINI3

Compact solutions that are particularly convenient to install.

The lifting units in the Wilo-DrainLift MINI3 series are both compact and ready-to-plug – they can be quickly and easily installed in a concealed wall. The Wilo-DrainLift MINI3-XS also comes in a WC version with a grinder pump. The factory setting is a WC connection on the front. If necessary, this connection can also be installed on the side. In the table below, you can see which lifting units can be replaced with new versions.

The right choice for new installations or replacements



Wilo-DrainLift MINI3	-XXS	-XS	-XS/WC with macerator
Size (W x H x D) in mm	299 x 170 x 159	389 x 266 x 167	389 x 266 x 169
Volume flow Q _{max} .	6 m ³ /h	6.5 m ³ /h	9 m ³ /h
Delivery head H _{max} .	5.5 m	8 m	9 m
Maximum temperature	40 °C (75 °C for max. 5 min)	40 °C (75 °C for max. 5 min)	40 °C (75 °C for max. 5 min)

These lifting units can be replaced with the new series!

Wilo (previous model)	HiDrainLift 3-24	HiDrainlift 3-35 HiDrainLift 3-37	HiSewlift 3-135 HiSewlift 3-15 HiSewlift 3-35
Grundfos	SOLOLift2 D-3	SOLOLift2 D-3	SOLOLift2 WC-1/3
Jung	HEBEFIX MINI	HEBEFIX plus	WCFIX 260
Saniflo SFA	Sanishower Flat Sanifloor	Sanidouche+ Saniaccess Sanispeed+	Saniaccess Sanibroy UP