

Wheel brushes Series 4000-6000 (D 180-250) for Stationary



Wheel Brushes in highly resistant crimped steel wire and with very high filament density. The 6000 Series, the diameter being equal, has 40% more filaments.

Applications: Deburring, satin finishing and polishing of surfaces of every material and shape. Suitable for industrial use.

D	ART	E	S	C	F	Ø mm	WIRE	MAX
180	4182	25	47	38	KIT mm	0,35	Steel	6000
180	4183	27	47	38	KIT mm	0,35	Steel	6000
180	4183	27	47	38	KIT mm	0,5	Steel	6000

D	ART	E	S	C	F	Ø mm	WIRE	MAX
180	4183	27	47	38	KIT mm	0,3	Stainless steel	6000
180	6183	25	30	58	KIT mm	0,35	Steel	6000
200	4202	23	47	38	KIT mm	0,35	Steel	6000
200	4202	23	47	38	KIT inch	0,35	Steel	6000
200	4203	29	47	38	KIT mm	0,2	Steel	6000
200	4203	29	47	38	KIT mm	0,35	Steel	6000
200	4203	29	47	38	KIT inch	0,35	Steel	6000
200	4203	29	47	38	KIT mm	0,5	Steel	6000
200	4203	29	47	38	KIT mm	0,3	Stainless steel	6000
200	*4203 sup	29	47	38	KIT mm	0,3	Stainless steel	6000
200	4203	29	47	38	KIT mm	0,3	Brass	6000
200	4204	36	47	38	KIT mm	0,35	Steel	6000
200	6203	30	40	58	KIT mm	0,35	Steel	6000
200	6203	30	40	58	KIT mm	0,5	Steel	6000
200	6203	30	40	58	KIT mm	0,3	Stainless steel	6000
250	6253	30	65	58	KIT mm	0,35	Steel	6000
250	6253	30	65	58	KIT mm	0,5	Steel	6000
250	6253	30	65	58	KIT mm	0,3	Stainless steel	6000
250	6254	42	65	58	KIT mm	0,35	Steel	6000