


## LSV 5-225 (600103000) Long-neck Sander

(220-240 V / 50 - 60 Hz); Tool Bag

Order no. 600103000 EAN 4007430282668











- For convenient sanding of primed surfaces on walls or ceilings
- Optimum balance when working, as the centre of gravity of the machine is not at the sanding head
- M-Clean technology: Effective extraction through the machine housing for maximum flexibility of the sanding head
- Sanding near edges, corners and adjoining sections time-saving and effective
- Ideal adaptation of the flexible sanding head to the surface for good work results
- Optimum extraction results thanks to spring-mounted brush rim that adapts to the surface.
- Vario-Constamatic (VC)-Full wave electronics for working at customised speeds to suit the application materials, and speeds that remain almost constant even under load
- Low weight reduces fatigue when working continuously
- Ergonomically shaped aluminium handle bar and T-handle for comfortable use in different positions
- Simple, quick and tool-free exchangeable shaft can be adjusted directly on site if needed
- Putting the machine down without kinking the hose and cable
- With extensive range of grinding media for every application
- Extraction possibility by means of connecting an all-purpose vacuum cleaner

www.metabo.com 1/2



Technical data	
Characteristics	
Sanding disc diameter	225 mm / 8 7/8 "
No-load speed	1000 - 1650 /min
Rated input power	500 W
Output power	270 W
Adjustable machine length	1.6 m / 61 7/32 "
Weight (without power cable)	3.8 kg / 8.38 lbs
Cable length	4 m / 157 1/2 "
Vibration	
Surface grinding	2.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s²
Noise emission	0,0
Sound pressure level	76 dB(A)
Sound power level (LwA)	87 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Sanding pad (very soft)

Coupling bush

Hexagonal wrench

Tool bag

Hook and loop sanding sheets with multi-perforation (1 each of P80, P100, P120, P150)
Flexible shaft (as replacement)

www.metabo.com 2/2