




WS 440 HF

[Overview](#) [Features](#) [Specifications](#) [Accessories](#) [Where To Buy](#)

Husqvarna WS 440 HF

WS 440 HF electric wall saw gives you increased possibilities for fast and efficient cutting in reinforced concrete, brick and other building materials, up to 530 mm thickness. Use this wall saw for all kinds of openings and sawing including stair, bevel and flush cutting. The user-friendly ergonomic design and ease of transport makes your job fast and efficient. WS 440 HF can be combined with CS 10, transforming it into a perfect wire saw.

-  Blade diameter, min **600 mm**
-  Blade diameter, max **1200 mm**
-  Cutting depth, max **530 mm**

Article number: WALL SAW WS 440 HF 1000 mm - 967 64 66-03

[Get quote](#) >

[Add to wish list](#) >

[Spare parts](#) | [Manuals](#)

Our local salesman can give you **price quotes**, **book a demo** or **give you a call** to talk more.



Motor

Output shaft RPM, max	1200 rpm
Max spindle torque	125 Nm
Spindle starting torque, Nm	100 Nm

Transmission

Number of gearbox speeds	1
--------------------------	----------

Sound and noise

Sound power level, guaranteed (LWA)	109 dB(A)
-------------------------------------	------------------

Cutting equipment

Arbor diameter	25,4/60 mm
Blade diameter, max	1200 mm
Blade diameter, min	600 mm
Cutting depth, max	530 mm
Starter blade diameter, max	1000 mm

Dimensions

Product size length	2200 mm
Product size width	900 mm
Product size height	800 mm
Weight	25 kg
Weight saw carriage	3.9 kg
Weight saw unit	25 kg

Other

Water flow, min	3.5 l/min
Water pressure, max	7 bar
Water temp at min flow, max	25 °C