

Husqvarna®

K 760 with OilGuard

Overview Features Specifications Accessories Media Where To Buy

Product_TextIcon_Expired

The Husqvarna K 760 Oilguard is specially designed to prevent engine damage resulting from an incorrect oil-fuel mixture. The K 760 Oilguard uses specially colored OilGuard oil, developed specifically for dusty environments like construction sites and ideal for air-cooled two-stroke engines. It is also possible to use standard two-stroke oil in a K 760 Oilguard, as the OilGuard feature can easily be deactivated. An optical detection system indicates if there is a sufficient amount of the correct type of oil in the fuel. The K 760 Oilguard also has features like the new generation of Active Air Filtration™, one of the market's most efficient centrifugal air cleaning systems that delivers up to one year's operation without a filter change and SmartCarb™, built-in automatic filter compensation and a highly efficient vibration dampening system. It is also outfitted with an X-Torq® engine, which reduces emissions up to 75 % and lowers fuel consumption by 20 % and DuraStarter™, a dust-sealed starter that boosts reliability and product life. Air Purge and a decompression valve make it very easy to start.

✿ Cutting depth, max	100 mm
✿ Blade diameter, max	300 mm
● Output power	3.7 kW

Daily exposure A(8) m/s²
Learn more about vibrations
[here](#)

0.9



Engine

Output power	3.7 kW
Cylinder displacement	73.5 cm³
Electrode gap	0.5 mm
Cylinders	1
Number of strokes	2-stroke engine

Dimensions

Product size length	601 mm
Product size width	225 mm
Product size height	389 mm
Weight	9.6 kg

Vibrations

Vibrations left/front handle	2.4 m/s²
Vibrations right/rear handle	2.4 m/s²

Cutting equipment

Cutting depth, max	100 mm
Blade diameter, max	300 mm
Arbor diameter	20/25,4 mm
Blade thickness, max	5 mm
Peripheral speed, max	80 m/s

Sound and noise

Sound power level, guaranteed (LWA)	115 dB(A)
Sound pressure level at operators ear	101 dB(A)

Certifications

Cert machine dir. 2006/42/EC Decl. No.

EURO TEST CERTIFICATE
SEC/10/2285